

## In-Wall Timer - Electronic Countdown Timer with Preset Times

Item EI220W-1



### PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

### FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from One hour to 8 hours
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

General	
Model Number	EI220W-1
Description	Electronic Countdown Timer with Preset Times
UPC Code	078275150287
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Time Presets	1 hr; 2 hrs; 4 hrs; 8 hrs
Operation Mode	Countdown
Countdown Time	8 hrs
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	

Color	White
Includes Wall Plate	No
Finish	Gloss

#### Load Ratings

Resistive Heater	15 A, 1800 W
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1 HP
Magnetic Ballast (NO) Range(s)	8 A, 1000 VA
General Purpose (NO) Range(s)	15 A, 120 VAC
Tungsten Incandescent Load Ratings NO Ranges	1000 W

#### Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Watts	1800
Hz	60
Amperage	15 A

#### Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

#### Packaging

Shipping Weight (lbs)	0.399
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

#### Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	Y