

Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Plastic Enclosure

Item PE153PF



PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

FEATURES

- ▶ Controls single- and two-speed pumps and cleaner/booster pumps
- ▶ Three ON/OFF events per circuit per day
- ▶ Seven preprogrammed modes
- ▶ Freeze and heater protection
- ▶ LCD readout
- ▶ Multi-voltage input and output
- ▶ Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

APPLICATIONS

- ▶ Heater Thermostat Control
- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

General

Model Number	PE153PF
Description	24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Plastic Enclosure
UPC Code	078275092402
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited

Control Specifications

Time Presets	Flexible
Operation Mode	24 hour
On Events	3 per circuit
Off Events	3 per circuit
Total Events	6 per circuit

Mechanical Specifications

Enclosure Type	Outdoor type 3R plastic
----------------	-------------------------

Dimensions

Product Dimensions (H x W x D) in	9.375 x 5.5 x 3.625 in
-----------------------------------	------------------------

Material Specifications

Color	Black
-------	-------

Communication Method

Has WiFi	No
----------	----

Load Ratings

Resistive (NO) Range(s)	17 A, 120/240 VAC
Motor Load Ratings Ranges	80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz
Tungsten Incandescent Load Ratings NO Ranges	5 A, 120/240 VAC

Electrical Specifications

Voltage Selection Type	Multi-Voltage
Input Voltage Range(s)	120/240 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	3-SPST
Hz	50/60
Amperage	17 A

Packaging

Shipping Weight (lbs)	2.744
Unit Carton Dimensions (H x W x L) in	5.501 x 12.001 x 13.751 in

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

ACCESSORIES



6T1396
Cover, Beige plastic