

Plug-In Timer - 7-Day Indoor Digital Plug-In Timer

Item DT620



PRODUCT DESCRIPTION

Full feature plug-in timer provides full 7-day programming with astronomical clock and Daylight Saving Time (DST) adjustment in a convenient plug-in for quick and easy automation.

FEATURES

- ▶ 28 ON/OFF programmable events
- ▶ Full 7-day programming options, including astronomical clock, automatic DST adjustment and random mode
- ▶ Two grounded receptacles and a grounded plug
- ▶ LR44 battery backup (included)
- ▶ Plugs directly into wall outlet

APPLICATIONS

- ▶ Air Movement & Ventilation
- ▶ Indoor Lighting Control

TECHNICAL DATA

General

Model Number	DT620
Description	7-Day Indoor Digital Plug-In Timer
UPC Code	078275125322
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Minimum ON/OFF Times	1 min
Operation Features	Astronomic
Operation Mode	7 day
Backup Type	Battery
Battery Type	LR44
Battery Service Type	Replaceable
Mechanism Type	Digital/Electrical
Application Compatibilities	CFL; LED
Chemical Composition of the Battery Cell	Alkaline
On Events	28
Off Events	28
Total Events	28

Mechanical Specifications

Number of Plugs	2
Plug Configurations	5-15

Dimensions

Product Dimensions (H x W x D) in	3.2 x 3.33 x 2.25 in
-----------------------------------	----------------------

Material Specifications

Color	White
-------	-------

Load Ratings

Resistive Heater	15 A, 120 VAC
Inductive Load Ratings NO Ranges	12 A, 120 VAC
Motor Load Ratings Ranges	1/2 HP, 120 VAC
Tungsten Incandescent Load Ratings NO Ranges	1000 W, 120 VAC

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Hz	60

Packaging

Shipping Weight (lbs)	0.509
Unit Carton Dimensions (H x W x L) in	3.375 x 3.375 x 3.062 in

Environmental Specifications

Usage Environments	Indoor
--------------------	--------

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	None
RoHS Certification	N/A