

## Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper

Item T8845PV



### PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

### FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Provides for every other day operation
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

### APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Landscape Water Control

### TECHNICAL DATA

#### General

Model Number	T8845PV
Description	Sprinkler/Irrigation Time Switch with 14-Day Skipper
UPC Code	078275700741
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Tripper Actuating Time	12 min
Mechanism Type	Analog/Mechanical
On Events	60
Off Events	60
Total Events	120

#### Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R plastic
Number of Trippers Included	12

#### Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
-----------------------------------	-----------------

#### Material Specifications

Color	Gray
-------	------

**Load Ratings**

Clock Motor Voltage	110/125 VAC, 60 Hz
Motor Load Ratings Ranges	24 VAC, 60 Hz

**Electrical Specifications**

Input Voltage Range(s)	24 VAC, 60 Hz
Switch Type	SPST
Load Voltage	24 VAC, 60 Hz
Hz	60
Amperage	20 VA

**Packaging**

Shipping Weight (lbs)	3.243
Unit Carton Dimensions (H x W x L) in	4.25 x 7.31 x 11.75 in

**Environmental Specifications**

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Lead
RoHS Certification	N/A


**ACCESSORIES**



**156T1950A**  
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



**133T700A**  
Micro Switch for T8800 and R8800 Series



**156T1954A**  
14 Skipper Pins for R8800, and T8800 Mechanical Water Heater Time Switch Series




**T104-20**  
Mechanical Water Heater Time Switch



**107T73**  
Replacement Day Wheel Pins for T8800 and R8800 Series



**107T119**  
Tripper (Silver) for T8800 and R8800 Series (Day Skipper)



**119T86A**  
24 VAC 20 VA Transformer, with #10 Ring Terminals



**124T2097**  
Insulator for R8806P101C, T8805P101C, T8845PV



**133T1115A**  
Toggle Switch for T8800 and R8800 Series

**156T1950AD12**  
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



**WG730-14D**  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG730-14DMX**  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG733-14D**  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG733-14DMX**  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**156T2978A**  
Package Accessory Trippers



**6T1339**  
Cover, Gray plastic



119T85  
Transformer - 24 V, 20 VA for  
T8845PV



WG736-14D  
480 V, 60 Hz Motor for T1900, T8800,  
R8800 Series