

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, Light Almond, Mexico Sales Only

Item EI200LAMX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from five minutes to 30 minutes
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI200LAMX
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, Light Almond, Mexico Sales Only
UPC Code	078275100572
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Time Presets	5 min; 10 min; 15 min; 30 min
Operation Mode	Countdown
Countdown Time	30 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in

Material Specifications

Color	Light Almond
-------	--------------

Load Ratings

Resistive Heater	15 A, 1800 W
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP
Magnetic Ballast (NO) Range(s)	8 A, 1000 VA
Tungsten Incandescent Load Ratings NO Ranges	1000 W

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Hz	60

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.4
Unit Carton Dimensions (H x W x D) in	2.251 x 2.881 x 4.751 in

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A