

In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Permanent Trippers, White

Item E1010



PRODUCT DESCRIPTION

These Heavy-Duty In-Wall Timers are ideal for turning on lights, fans, pumps and other heavy duty loads for energy savings, security and convenience. The timer provides up to 12 ON and 12 OFF operations per day.

FEATURES

- ▶ E1010 includes one ON/OFF permanently attached tripper for single ON/OFF control per 24-hour period
- ▶ E1020 includes two ON/OFF trippers and can accommodate up to 12 ON/OFF trippers
- ▶ Programmable in 30-minute intervals
- ▶ Turns ON/OFF heavy-duty loads for energy savings, security and convenience
- ▶ Mounts to any standard junction box
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	E1010
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Permanent Trippers, White
UPC Code	078275440005
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Minimum ON/OFF Times	30 min
Operation Mode	24 hour
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL
On Events	1
Off Events	1
Total Events	2

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.25 x 3.25 x 1.375 in
-----------------------------------	------------------------

Material Specifications

Color	White
-------	-------

Includes Wall Plate	Yes
---------------------	-----

Load Ratings

Motor Load Ratings Ranges	12 FLA @ 125 VAC, 60 Hz
Resistive (NO) Range(s)	15 A, 125 VAC
Incandescent Single Gang Load Ratings Ranges	1500 W, 125 VAC

Electrical Specifications

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST-NO
Neutral Connection Required	Yes
Hz	60

Environmental Specifications

Temperature (operation)	-4 - 77 °F / -20 - 25 °C
-------------------------	--------------------------

Packaging

Shipping Weight (lbs)	0.748
Unit Carton Dimensions (H x W x D) in	3.251 x 3.501 x 5.501 in

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

ACCESSORIES



156EB1945A
Trippers for E1020 (Pack of 2)



48EB937
Spring - Cam Passivate for E1020 and WH21



48EB938
Spring - Cam Green for E1020 and WH21



WG230-13
Motor - 125 V 60 Hz with Leads & Cover