

## Electronic Timer Control - All-Purpose Photocontrol Contractor Box, 208-220 VAC 50/60 Hz; 208-240 VAC 60 Hz, DPST, Outdoor Metal Enclosure

Item PCCB32A2PLC4513MX



### PRODUCT DESCRIPTION

The PCCB32A2PLC4513MX all-purpose Photocontrol Contractor box provides an easy-to-install solution for a variety of application needs. It comes with a pre-installed 3-pin photocontrol receptacle, 32 A 2-pole Contactor, 40 A 2-pole circuit breaker, and Twist Lock Photocontrol.

### FEATURES

- ▶ Built-in 32 A 2-pole contactor.
- ▶ Built-in 40 A 2-pole circuit breaker for turning off the load that is being controlled.
- ▶ Built-in 3-pin photocontrol receptacle.
- ▶ Twist-lock photocontrol operated (included).

### TECHNICAL DATA

#### General

Model Number	PCCB32A2PLC4513MX
Description	All-Purpose Photocontrol Contractor Box, 208-220 VAC 50/60 Hz; 208-240 VAC 60 Hz, DPST, Outdoor Metal Enclosure
UPC Code	078275157736
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

#### Control Specifications

Operation Features	Photocontrol Operated
On Events	Photocontrol Operated
Off Events	Photocontrol Operated
Total Events	Photocontrol Operated

#### Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R metal
----------------	------------------------------

#### Dimensions

Product Height (in)	11.12
Product Height (mm)	284.48
Product Width (in)	9.6
Product Width (mm)	243.84
Product Depth (in)	4
Product Depth (mm)	101.6
Wire Size Min	Contactor #14 AWG, Circuit Breaker #14 AWG
Wire Size Max	Contactor #10 AWG, Circuit Breaker #6 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Left	(1) combination 1/2" - 3/4"

Knockout Dimensions Right

(1) combination 1/2" - 3/4"

**Material Specifications**

Color	Gray
Body Material	Metal

**Communication Method**

Has WiFi	No
----------	----

**Load Ratings**

Resistive (NO) Range(s)	32 A
General Purpose (NO) Range(s)	32 A

**Electrical Specifications**

Wiring Option	Wire leads
Input Voltage Range(s)	208-220 VAC 50/60 Hz; 208-240 VAC, 60 Hz
Switch Type	DPST
Hz	50/60

**Packaging**

Shipping Weight (lbs)	8.5
Unit Carton Dimensions (H x W x D) in	6.75 x 12.5 x 14.5 in

**Standards and Certifications**

Other Certifications and Compatibilities	Green Energy
California Proposition 65	None
RoHS Certification	N/A