

In-Wall Timer - Electronic Countdown Timer, 125 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, White

Item EI235W



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

FEATURES

- ▶ No programming required.
- ▶ Provides silent operation in time ranges from 15 minutes to 2 hours.
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation.
- ▶ Replaces single-pole switches in a variety of applications.
- ▶ Incandescent/fluorescent/CFL/LED compatible.
- ▶ For use with decorator-style wall plate (not included).
- ▶ Requires neutral connection.

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI235W
Description	Electronic Countdown Timer, 125 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, White
UPC Code	078275111202
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Time Presets	15 min; 30 min; 45 min; 1 hr; 2 hrs
Operation Mode	Countdown
Countdown Time	2 hrs
Hold Mode Included	No
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in

Material Specifications

Color	White
Includes Wall Plate	No
Finish	Gloss

Load Ratings

Resistive Heater	15 A, 1800 W
Electronic Ballast LED	4 A, 500 VA
Magnetic Ballast (NO) Range(s)	8 A, 1000 VA
Tungsten Incandescent Load Ratings NO Ranges	1000 W

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Watts	1800
Hz	60
Amperage	15 A

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.4
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	Y