

## In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, White

Item EI200W



### PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- ▶ No programming required.
- ▶ Provides silent operation in time ranges from five minutes to 30 minutes.
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation.
- ▶ Replaces single-pole switches in a variety of applications.
- ▶ Incandescent/fluorescent/CFL/LED compatible.
- ▶ For use with decorator-style wall plate (not included).
- ▶ Requires neutral connection.

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

General	
Model Number	EI200W
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 5,10,15,30 Minute, With Hold, White
UPC Code	078275095199
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Time Presets	5 min; 10 min; 15 min; 30 min
Operation Mode	Countdown
Countdown Time	30 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in

**Material Specifications**

Color	White
-------	-------

**Load Ratings**

Resistive Heater	15 A, 1800 W
Electronic Ballast LED	4 A, 500 VA
Magnetic Ballast (NO) Range(s)	8 A, 1000 VA
Tungsten Incandescent Load Ratings NO Ranges	1000 W

**Electrical Specifications**

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST-NO
Neutral Connection Required	Yes
Hz	60
Amperage	15 A

**Environmental Specifications**

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

**Packaging**

Shipping Weight (lbs)	0.349
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	Y