

In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 60 Minute Max, Without Hold, Ivory, Mexico Sales Only

Item FD60MCMX



PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 60-minute timer
- ▶ SPST (Single-Pole Single-Throw)
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single- or multi-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Breaks circuit at end of timing cycle
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ No neutral connection is required

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General

Model Number	FD60MCMX
Description	Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 60 Minute Max, Without Hold, Ivory, Mexico Sales Only
UPC Code	078275005051
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Time Presets	60 min
Operation Mode	Countdown
Countdown Time	60 min
Hold Mode Included	No
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

Wall Plate Configurations	Single-Gang; Multi-Gang
---------------------------	-------------------------

Dimensions

Product Dimensions (H x W x D) in

4.125 x 1.75 x 1.25 in

Material Specifications

Color Ivory

Load Ratings

Resistive Heater 20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC

Tungsten Incandescent Load Ratings NO Ranges 7 A, 125 VAC, 875 W

Electrical Specifications

Input Voltage Range(s) 125-277 VAC, 50/60 Hz

Wiring Configurations Single

Switch Type SPST

Neutral Connection Required No

Hz 50/60

Amperage 20 A

Environmental Specifications

Temperature (operation) 32 - 104 °F / 0 - 40 °C

Packaging

Shipping Weight (lbs) 0.3

Unit Carton Dimensions (H x W x D) in 7 x 4 x 2.5 in

Standards and Certifications

CSA Certification cCSAus

Other Certifications and Compatibilities NOM

California Proposition 65 None

RoHS Certification N/A

ACCESSORIES



FD60MP
Plate for 60-Min without HOLD, Ivory
(FD460M, FD60MC)



146--00045
Knob-Wall Switch FD Series - Ivory



146--00046
Knob-Wall Switch FD Series - White



146--00047
Knob-Wall Switch FD Series - Almond



146MT416A
Knob-Wall Switch FD Series - Black