

## In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 2 Hour Max, Without Hold, Ivory, Mexico Sales Only

Item FD2HMX



### PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- ▶ 2-Hour timer
- ▶ SPST (Single-Pole Single-Throw)
- ▶ Breaks circuit at end of timing cycle
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single- or multi-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ No neutral connection is required

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

#### General

Model Number	FD2HMX
Description	Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 2 Hour Max, Without Hold, Ivory, Mexico Sales Only
UPC Code	078275073999
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

#### Control Specifications

Operation Mode	Countdown
Countdown Time	2 hrs
Hold Mode Included	No
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang; Multi-Gang
---------------------------	-------------------------

#### Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.25 in
-----------------------------------	------------------------

**Material Specifications**

Color	Ivory
-------	-------

**Load Ratings**

Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten Incandescent Load Ratings NO Ranges	7 A, 125 VAC, 875 W

**Electrical Specifications**

Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	No
Hz	50/60

**Environmental Specifications**

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

**Packaging**

Shipping Weight (lbs)	0.301
Unit Carton Dimensions (H x W x D) in	4.63 x 2.13 x 2.88 in

**Standards and Certifications**

UL Certification	UL
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

---

## ACCESSORIES



148FD5075  
Plate for 2-Hr without HOLD, Ivory  
(FD2H, FD32H)



146--00045  
Knob-Wall Switch FD Series - Ivory



146--00046  
Knob-Wall Switch FD Series - White



146--00047  
Knob-Wall Switch FD Series - Almond



146MT416A  
Knob-Wall Switch FD Series - Black