

## Electronic Timer Control - Astronomic 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor Metal Enclosure, Mexico Sales Only

Item ET8115CMX

**NOM**

### PRODUCT DESCRIPTION

This series offers an easy way to upgrade from a basic mechanical time switch to an electronic time switch. These timers will allow for up-to-the-minute programming, battery backup for power loss, up to 28 events total, and automatic daylight saving time corrections without the need of user interaction. They come in standard 7-day astronomic versions.

### FEATURES

- ▶ Selector switch to determine input voltage between 120-277 VAC
- ▶ Up to 28 events total
- ▶ To-the-minute accuracy
- ▶ Temporary override or permanent manual override
- ▶ Automatic Daylight Saving Time adjustment
- ▶ Astronomic models enable dusk-to-dawn scheduling

### APPLICATIONS

- ▶ Outdoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

### TECHNICAL DATA

General	
Model Number	ET8115CMX
Description	Astronomic 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor Metal Enclosure, Mexico Sales Only
UPC Code	078275089778
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Operation Features	Astronomic
Operation Mode	7 day
Daylight Savings Adjustment	Automatic
Backup Type	Battery
Battery Type	AAA
Battery Service Type	Field Serviceable
On Events	14
Off Events	14
Total Events	28 (+ Astronomic)

Mechanical Specifications	
Enclosure Type	Indoor type 1 metal

Dimensions	
------------	--

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.4375 in
-----------------------------------	---------------------------

Wire Size Min	#14 AWG
---------------	---------

Wire Size Max	#8 AWG
---------------	--------

#### Communication Method

Has WiFi	No
----------	----

#### Load Ratings

Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
--------------------------------	-------------------

Resistive (NO) Range(s)	20 A, 28 VDC; 30 A, 120/240 VAC
-------------------------	---------------------------------

Inductive Load Ratings NO Ranges	30 A, 120/240 VAC
----------------------------------	-------------------

Motor Load Ratings NO Ranges	1 HP @ 120 VAC; 2 HP @ 240 VAC
------------------------------	--------------------------------

Tungsten Incandescent Load Ratings NO Ranges	5 A, 120-240 VAC
--	------------------

#### Electrical Specifications

Voltage Selection Type	Selector Switch
------------------------	-----------------

Wiring Option	Terminals
---------------	-----------

Input Voltage Range(s)	120-277 VAC, 50/60 Hz
------------------------	-----------------------

Number of Circuits	1
--------------------	---

Switch Type	SPDT
-------------	------

Maximum Power Consumption (W)	6 W
-------------------------------	-----

Electronic Series	ET8000 Series
-------------------	---------------

Hz	50/60
----	-------

#### Packaging

Shipping Weight (lbs)	2.851
-----------------------	-------

Unit Carton Dimensions (H x W x L) in	3.131 x 5.251 x 8.001 in
---------------------------------------	--------------------------

#### Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

Other Certifications and Compatibilities	NOM
--	-----

California Proposition 65	None
---------------------------	------

---

## ACCESSORIES



ET-NF

RC Snubber Noise Filter 24-277 VAC for Electronic Controls