

Electronic Timer Control - Expanded 4-Pole Lighting Contractor Box, 120 - 600 VAC, 60 Hz, 4PST, Outdoor Metal Enclosure

Item ETCB28254PCR



PRODUCT DESCRIPTION

The ETCB28254PCR Expanded 4-Pole lighting contractor box provides an easy-to-install solution for a variety of application needs. The contractor box comes with a pre-installed astronomic timer with 7-day, holiday/exception period scheduling, USB for schedule transfer and backup, an electrically held 40 A contactor, as well as inputs for overrides and surge protective devices.

FEATURES

- ▶ 7-Day/365-day astronomic scheduling.
- ▶ Up to 96 scheduling set points.
- ▶ Up to 50 holiday/exception period set points.
- ▶ USB port for backing up or transferring schedules.
- ▶ Built-in 40 A, 4-pole contactor for more robust loads.
- ▶ Input for optional "timed" photo control override.
- ▶ Input for other types of switches/sensors.
- ▶ Terminals for adding surge protection.
- ▶ 100-hour supercapacitor eliminates the need for battery replacement.
- ▶ Requires 120 VAC, 60 Hz for powering the control.

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

TECHNICAL DATA

General

Model Number	ETCB28254PCR
Description	Expanded 4-Pole Lighting Contractor Box, 120 - 600 VAC, 60 Hz, 4PST, Outdoor Metal Enclosure
UPC Code	078275159181
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications

Minimum ON/OFF Times	1 min
Minimum Pulse Time	2 sec
Maximum ON/OFF Times	Indefinite
Time Presets	Flexible
Operation Features	Astronomic; Holiday; Override
Backup Type	Supercapacitor
Backup Protection Time	100 Hour
On Events	48
Off Events	48
Total Events	96 (+ Astronomic)

Mechanical Specifications

Enclosure Type Indoor/outdoor type 3 metal

Dimensions

Product Dimensions (H x W x D) in	11.75 x 10 x 4.75 in
Wire Size Min	#14 AWG
Wire Size Max	#4 AWG (Load Side)
Knockout Dimensions Bottom	(7) 1/2" - 3/4" combination, (2) 3/4" - 1" combination
Knockout Dimensions Back	(4) 1/2" - 3/4" combination, (1) 3/4" - 1" combination
Knockout Dimensions Left	(4) 1/2" - 3/4" combination
Knockout Dimensions Right	(4) 1/2" - 3/4" combination

Material Specifications

Color Gray

Communication Method

Has WiFi No

Load Ratings

Electronic Ballast LED	16 A, 120/277 VAC
Resistive (NO) Range(s)	40 A
General Purpose (NO) Range(s)	40 A
Motor Load Ratings NO Ranges	32 A, 240-600 VAC FLA; 180 A, 240/277 VAC LRA; 150 A, 480 VAC LRA; 120 A, 600 VAC LRA; 5 HP @ 240/277 VAC (1-Phase); 10 HP @ 240/277 VAC (3-Phase); 15 HP @ 480 VAC (3-Phase); 20 HP @ 600 VAC (3-Phase)

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Switch Type	4xSPST
Electronic Series	ETCB Series
Hz	60
Amperage	40 A

Packaging

Shipping Weight (lbs)	14
Unit Carton Dimensions (H x W x L) in	6.375 x 13.25 x 13.5 in

Environmental Specifications

Temperature (operation) -40 °F to 104 °F / (-40 °C to 40 °C)

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Nickel; Lead
RoHS Certification	N/A