

In-Wall Timer - Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, SPST, 5 Minute Max, With Hold, Silver, Mexico Sales Only

Item FF5MHMX

**NOM**

PRODUCT DESCRIPTION

The FF Series Commercial Countdown Timers are designed to replace any standard wall switch and do not require electricity to operate. These energy-efficient switches automatically limit the ON times for fans, lighting, motors, heaters, and other energy consuming loads. A commercial "brushed metal" look plate (plastic construction) meets NEC requirements. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 5-Minute timer with hold
- ▶ SPST (Single-Pole Single-Throw)
- ▶ Breaks circuit at end of timing cycle
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Brushed metal look switch plate meets NEC requirements (plate is included)
- ▶ Incandescent/fluorescent/CFL/LED compatible

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General

Model Number	FF5MHMX
Description	Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, SPST, 5 Minute Max, With Hold, Silver, Mexico Sales Only
UPC Code	078275184114
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Operation Mode	Countdown
Countdown Time	5 min
Hold Mode Included	Yes
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

Wall Plate Configurations	Single-Gang; Multi-Gang
---------------------------	-------------------------

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.25 in
-----------------------------------	------------------------

Material Specifications

Color	Silver
Includes Wall Plate	Yes
Finish	Brushed Metal

Load Ratings

Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten Incandescent Load Ratings NO Ranges	7 A, 125 VAC, 875 W

Electrical Specifications

Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	No
Hz	50/60

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.351
Unit Carton Dimensions (H x W x D) in	4.63 x 2.13 x 2.88 in

Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A