

## In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, Timer Only, 120 VAC, 20A, 1 Gang, SPST, White

Item KM2ST-1G



### PRODUCT DESCRIPTION

For installing on circuits up to 20 A, this timer provides automatic 24-hour ON/OFF control of outdoor/indoor lighting, fans, pumps, office equipment and other types of loads. Wall plate not included.

### FEATURES

- ▶ 72 trippers provide 36 ON/OFF events per 24-hour period
- ▶ Captive trippers with 20-minute switching intervals
- ▶ 3-way (SPDT) switch available
- ▶ 3-position ON/OFF/AUTO override provides continuous ON or OFF operation
- ▶ Reliable synchronous timer motor
- ▶ Multiple wall plates available
- ▶ Easy wiring and installation
- ▶ Heavy-Duty 20 A rating
- ▶ Requires neutral connection

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

### TECHNICAL DATA

General	
Model Number	KM2ST-1G
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, Timer Only, 120 VAC, 20A, 1 Gang, SPST, White
UPC Code	078275153660
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications	
Minimum ON/OFF Times	20 min
Operation Mode	24 hour
Hold Mode Included	No
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL
On Events	36
Off Events	36
Total Events	72

Mechanical Specifications	
Wall Plate Configurations	Single-Gang

Material Specifications	
Color	White

Includes Wall Plate	No
Finish	Matte

#### Communication Method

Has WiFi	No
Has Bluetooth	No

#### Load Ratings

Resistive (NO) Range(s)	20 A, 120 VAC
Inductive Load Ratings NO Ranges	8 A, 120 VAC
Incandescent Single Gang Load Ratings Ranges	1350 W, 120 VAC

#### Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	Yes
Wiring Option	SPST (3) #14 AWG color coded; SPDT (4) #14 AWG color coded
Hz	60
Amperage	20 A

#### Environmental Specifications

Operating Humidity	0 to 95%, Non-condensing
Temperature (operation)	-40 - 180 °F / -40 - 82 °C
Usage Environments	Indoor; Outdoor

#### Packaging

Shipping Weight (lbs)	0.379
Unit Carton Dimensions (H x W x D) in	3 x 3 x 4 in

#### Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

---

## ACCESSORIES



24--00109

Wall Plate for KM2ST-1G or KM2STU-1G, Single Gang, White