

## Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Metal Enclosure

Item PE153F



### PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

### FEATURES

- ▶ Controls single- and two-speed pumps and cleaner/booster pumps
- ▶ Three ON/OFF events per circuit per day
- ▶ Seven preprogrammed modes
- ▶ Freeze and heater protection
- ▶ LCD readout
- ▶ Multi-voltage input and output
- ▶ Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

### APPLICATIONS

- ▶ Heater Thermostat Control
- ▶ Motor Control
- ▶ Pump Control

### TECHNICAL DATA

#### General

Model Number	PE153F
Description	24-Hour Electronic Time Control, 3-Circuit, Freeze Protection Probe, Type 3R Metal Enclosure
UPC Code	078275092365
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited

#### Control Specifications

Time Presets	Flexible
Operation Mode	24 hour
On Events	3 per circuit
Off Events	3 per circuit
Total Events	6 per circuit

#### Mechanical Specifications

Enclosure Type	Outdoor type 3R metal
----------------	-----------------------

#### Dimensions

Product Dimensions (H x W x D) in	9.375 x 5.5 x 3.625 in
-----------------------------------	------------------------

#### Material Specifications

Color	Black
-------	-------

**Communication Method**

Has WiFi	No
----------	----

**Load Ratings**

Resistive (NO) Range(s)	17 A, 120/240 VAC
Motor Load Ratings NO Ranges	80 LRA @ 120/240 VAC; 17 FLA @ 120/240 VAC
Tungsten Incandescent Load Ratings NO Ranges	5 A, 120/240 VAC

**Electrical Specifications**

Voltage Selection Type	Multi-Voltage
Input Voltage Range(s)	120/240 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	3-SPST
Hz	50/60
Amperage	17 A

**Packaging**

Shipping Weight (lbs)	4.151
Unit Carton Dimensions (H x W x L) in	4.253 x 7.253 x 11.623 in

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A