

## Portable Outdoor Timer - Two-Circuit Portable Outdoor Timer with Photocontrol

Item P1251P



### PRODUCT DESCRIPTION

Use these convenient plug-in timers instead of hard-wired controls. They offer plug-in receptacles for convenience and ease of use. They have built-in GFCI protected circuits.

### FEATURES

- ▶ 24-hour with 23 ½-hour MAX ON time
- ▶ Timed circuit controlled by timer
- ▶ Timed and photocontrol circuit controlled by photocell and timer (P1251P only)
- ▶ Built-in GFCI protected circuits and three-prong grounded plug for time switch supply
- ▶ Type 3R plastic indoor/outdoor enclosure
- ▶ 2 ON/OFF trippers standard
- ▶ Accepts up to 12 sets of trippers

### APPLICATIONS

- ▶ Landscape Lighting
- ▶ Motor Control
- ▶ Pump Control

### TECHNICAL DATA

#### General

|                                |  |
|--------------------------------|--|
| Model Number                   | P1251P   |
| Description                    | Two-Circuit Portable Outdoor Timer with Photocontrol |
| UPC Code                       | 078275122147   |
| Brand                          | Intermatic   |
| Country of Origin (Intermatic) | MEXICO   |
| Warranty Period                | 1-Year limited                                       |

#### Control Specifications

|                |         |
|----------------|---------|
| Operation Mode | 24 hour |
|----------------|---------|

#### Mechanical Specifications

|                     |                                |
|---------------------|--------------------------------|
| Plug Configurations | 5-15                           |
| Enclosure Type      | Indoor/outdoor type 3R plastic |

#### Dimensions

|                                   |   |
|-----------------------------------|---|
| Product Dimensions (H x W x D) in | 9.375 x 5.5 x 4 in                            |
| Cord Size                         | 3 wire, outdoor grade, 24" with grounded plug |
| Cord Length (ft)                  | 2   |
| Cord Length (m)                   | 0.61  |

#### Material Specifications

|       |       |
|-------|-------|
| Color | Beige |
|-------|-------|

#### Load Ratings

|  |                                |
|--|--------------------------------|
| Motor Load Ratings NO Ranges                 | 1 HP, 15 FLA, 90 LRA @ 120 VAC |
| Tungsten Incandescent Load Ratings NO Ranges | 15 A, 1800 W                   |

**Packaging**

|                                       |                 |
|---------------------------------------|-----------------|
| Shipping Weight (lbs)                 | 2.744           |
| Unit Carton Dimensions (H x W x L) in | 10.5 x 7 x 4 in |

**Standards and Certifications**

|  |              |
|--|--------------|
| CSA Certification                        | cCSAus       |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | DEHP         |
| RoHS Certification                       | N/A          |

---

## ACCESSORIES



107TN221

Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222

Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS