

## Item Bundle - 60 A Load Center with T101M Mechanism, 4-Breaker Spaces

Item T21001R



### PRODUCT DESCRIPTION

This system can be used as a load center only, or add a heavy-duty mechanical time switch or wiring devices for a complete system.

### FEATURES

- ▶ Four breaker spaces
- ▶ Accepts PF1000M, P1403ME, P1353ME, P4043ME, P4243ME, T100M or RC2000M Series mechanisms
- ▶ Accepts many interchangeable type breakers
- ▶ Load center dead front has two knockouts for switches or GFCIs and one on the side
- ▶ Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately

### APPLICATIONS

- ▶ Distribution/Control Panel
- ▶ Motor Control
- ▶ Pump Control

### TECHNICAL DATA

#### General

|                                |   |
|--------------------------------|---|
| Model Number                   | T21001R   |
| Description                    | 60 A Load Center with T101M Mechanism, 4-Breaker Spaces |
| UPC Code                       | 078275083455  |
| Brand                          | Intermatic  |
| Country of Origin (Intermatic) | MEXICO  |
| Warranty Period                | 1-Year limited  |

#### Mechanical Specifications

|                             |                |
|-----------------------------|----------------|
| Number of Breaker Knockouts | 4              |
| Enclosure Type              | 3R Beige metal |

#### Dimensions

|                                   |   |
|-----------------------------------|---|
| Product Dimensions (H x W x D) in | 16.875 x 8.875 x 4.75 in                                  |
| Knockout Dimensions Bottom        | (5) combination 1/2" - 3/4" and (3) combination 3/4" - 1" |
| Knockout Dimensions Back          | (1) combination 1/2" - 3/4" and (1) 3/4" - 1"             |
| Knockout Dimensions Left          | (1) combination 1/2" - 3/4"                               |
| Knockout Dimensions Right         | (1) 1 3/4" x 2 3/4"                                       |

#### Material Specifications

|       |       |
|-------|-------|
| Color | Beige |
|-------|-------|

#### Load Ratings

|                            |  |
|----------------------------|--|
| Load Center Ratings        | 60 A, 120-208 VAC, 60 Hz; 60 A, 240 VAC, 60 Hz, Single Phase |
| Pilot Duty (NO) Range(s)   | 1000 VA, 120-240 VAC   |
| Load Center Rating Display | 60 A, 120/240 VAC or 120/208 VAC, Single Phase               |
| Mechanism Supply Voltage   | 120 VAC, 60 Hz   |

|  |  |
|--|--|
| Mechanisms                                   | T101M  |
| Motor Load Ratings NO Ranges                 | 2 HP, 24 FLA @ 120 VAC; 5 HP, 28 FLA @ 240 VAC |
| Tungsten Incandescent Load Ratings NO Ranges | 40 A, 120-240 VAC                              |

**Electrical Specifications**

|                                       |      |
|---------------------------------------|------|
| Number of Circuits                    | 1    |
| Switch Type                           | SPST |
| Maximum Power Consumption (W)         | 3 W  |
| Number of Receptacle/Switch Knockouts | 2    |
| Hz                                    | 60   |

**Packaging**

|                                       |                      |
|---------------------------------------|----------------------|
| Shipping Weight (lbs)                 | 12.225               |
| Unit Carton Dimensions (H x W x L) in | 5.75 x 10 x 17.75 in |

**Environmental Specifications**

|                         |                                      |
|-------------------------|--------------------------------------|
| Temperature (operation) | -40 °F to 130 °F / (-40 °C to 54 °C) |
|-------------------------|--------------------------------------|

**Standards and Certifications**

|  |              |
|--|--------------|
| CSA Certification                        | cCSAus       |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | Lead         |
| RoHS Certification                       | N/A          |

**ACCESSORIES**



156T1978A  
Extra/replacement trippers 1 ON and 2 OFF



21T156A  
Spacer-Standoff, 3" long - 4 pack



21T166A  
Spacer-Standoff, 3" long - 2 pack



156T2978A  
Package Accessory Trippers



22T338GR  
Mounting Bracket for Intermatic Standardized Timer Mechanisms

22T713  
Bracket Painted

8--00008A  
Latch-Enclosure

124--00139A  
4-Pole Buss Bar Assembly

156PA13715A  
1" Nonmetallic Hub Kit