

## Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper

Item T8805P101C



### PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

### FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Provides for every other day operation
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

### APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Landscape Water Control

### TECHNICAL DATA

General	
Model Number	T8805P101C
Description	Sprinkler/Irrigation Time Switch with 14-Day Skipper
UPC Code	078275700758
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Tripper Actuating Time	12 min
Mechanism Type	Analog/Mechanical
On Events	60
Off Events	60
Total Events	120
Mechanical Specifications	
Enclosure Type	Indoor/outdoor type 3R plastic
Number of Trippers Included	12
Dimensions	
Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Material Specifications	
Color	Gray

**Load Ratings**

Clock Motor Voltage	125 VAC, 60 Hz
Motor Load Ratings NO Ranges	1/2 HP @ 120 VAC

**Electrical Specifications**

Input Voltage Range(s)	125 VAC, 60 Hz
Switch Type	SPST
Load Voltage	125 VAC, 60 Hz
HP	1/2
Hz	60
Amperage	15 A

**Packaging**

Shipping Weight (lbs)	2.75
Unit Carton Dimensions (H x W x L) in	4.251 x 7.251 x 11.751 in

**Environmental Specifications**

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Lead
RoHS Certification	N/A


ACCESSORIES



156T1950A  
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



133T700A  
Micro Switch for T8800 and R8800 Series



156T1954A  
14 Skipper Pins for R8800, and T8800 Series



107T73  
Replacement Day Wheel Pins for T8800 and R8800 Series



107T119  
Tripper (Silver) for T8800 and R8800 Series (Day Skipper)



124T2097  
Insulator for R8806P101C, T8805P101C, T8845PV



133T1115A  
Toggle Switch for T8800 and R8800 Series

156T1950AD12  
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



WG730-14D  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG730-14DMX  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14D  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14DMX  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



156T2978A  
Package Accessory Trippers



6T1339  
Cover, Gray plastic



WG736-14D  
480 V, 60 Hz Motor for T1900, T8800, R8800 Series