

## Mechanical Time Switch - 24-Hour Mechanical Time Switch with Skip-a-Day, 208-277 VAC, 60Hz, SPDT, Indoor Metal Enclosure, 15 Minute Interval

Item T1976



### PRODUCT DESCRIPTION

This series of mechanical time switches offers more flexible scheduling capabilities by offering 15-minute intervals. These units also come with trippers that slide in or out easily for fast and accurate settings. All units can control up to 20 A of electrical load and have a single pole, double throw switch.

### FEATURES

- ▶ Provides up to 96 operations (48 ON/48 OFF) every 24 hours
- ▶ Models with skipper wheel allow for operations to be omitted on selected days of the week
- ▶ 15-minute intervals
- ▶ Captive trippers slide in and out of dial for fast, accurate setting

### APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control

### TECHNICAL DATA

General	
Model Number	T1976
Description	24-Hour Mechanical Time Switch with Skip-a-Day, 208-277 VAC, 60Hz, SPDT, Indoor Metal Enclosure, 15 Minute Interval
UPC Code	078275194212
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Minimum ON/OFF Times	15 min
Skipper Wheel	24 Hour
Operation Mode	24 hour
Has Manual Override	Yes
On Events	48
Off Events	48
Total Events	96
Mechanical Specifications	
Enclosure Type	Indoor type 1 metal
Number of Trippers Included	96
Dimensions	
Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#12 AWG

### Material Specifications

Color Gray

### Load Ratings

Resistive (NO) Range(s) 20 A, 125-480 VAC

Motor Load Ratings NO Ranges 1/2 HP @ 125 VAC; 1 HP @ 250 VAC

### Electrical Specifications

Wiring Option Terminals

Input Voltage Range(s) 208-277 VAC, 60 Hz

Number of Circuits 1

Switch Type SPDT

Maximum Power Consumption (W) 3 W

Hz 60

### Packaging

Shipping Weight (lbs) 2.744

Unit Carton Dimensions (H x W x L) in 8.25 x 3.5 x 5.5 in

### Environmental Specifications

Temperature (operation) -40 °F to 130 °F / (-40 °C to 54 °C)

### Standards and Certifications

CSA Certification cCSAus

Other Certifications and Compatibilities Green Energy


California Proposition 65 Lead

RoHS Certification N/A

**ACCESSORIES**



**156T1950A**  
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



**22T338GR**  
Mounting Bracket for Intermatic Standardized Timer Mechanisms



**124T905**  
Insulator for T1905HDM, T1975EHDM, T1975HD, T1976, T1975, T1975ER, T1905



**133T698A**  
Replacement Snap Switch for T1970 Series



**WG730-14D**  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG730-14DMX**  
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG733-14D**  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**WG733-14DMX**  
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



**156T1957A**  
Skipper Screws (3 per package)



**156T2978A**  
Package Accessory Trippers



**WG736-14D**  
480 V, 60 Hz Motor for T1900, T8800, R8800 Series