


Mechanical Time Switch - 24-Hour Mechanical Time Switch, 208-277 VAC, 60Hz, SPDT, Indoor Metal Enclosure, 15 Minute Interval, Mexico Sales Only

Item T1906MX

**NOM**

PRODUCT DESCRIPTION

This series of mechanical time switches offers more flexible scheduling capabilities by offering 15-minute intervals. These units also come with trippers that slide in or out easily for fast and accurate settings. All units can control up to 20 A of electrical load and have a single pole, double throw switch.

FEATURES

- ▶ Provides up to 96 operations (48 ON/48 OFF) every 24 hours
- ▶ Models with skipper wheel allow for operations to be omitted on selected days of the week
- ▶ 15-minute intervals
- ▶ Captive trippers slide in and out of dial for fast, accurate setting

APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control

TECHNICAL DATA

General

Model Number	T1906MX
Description	24-Hour Mechanical Time Switch, 208-277 VAC, 60Hz, SPDT, Indoor Metal Enclosure, 15 Minute Interval, Mexico Sales Only
UPC Code	078275193215
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Minimum ON/OFF Times	15 min
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
On Events	48
Off Events	48
Total Events	96

Mechanical Specifications

Enclosure Type	Indoor type 1 metal
Number of Trippers Included	96

Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#12 AWG

Load Ratings

Resistive (NO) Range(s)	20 A, 125-480 VAC
Motor Load Ratings NO Ranges	1/2 HP @ 125 VAC; 1 HP @ 250 VAC

Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	3 W
Hz	60

Packaging

Shipping Weight (lbs)	2.745
Unit Carton Dimensions (H x W x L) in	8.25 x 3.5 x 5.5 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



124T907A
Insulator Assembly (S001)



133T701A
Replacement Snap Switch for T1900
and T2000 Series



156T1950A
Set of 12 Trippers for T1900, T2000,
C8800, R8800 and T8800 Series

156T1950AD12
12 Bags of 156T1950A Trippers for
T1900, T2000, C8800, R8800, and
T8800 Series



WG730-14D
125 VAC, 60 Hz Motor for R8800,
T1900, T1970, and T8800 Series



WG730-14DMX
125 VAC, 60 Hz Motor for R8800,
T1900, T1970, and T8800 Series



WG733-14D
208-277 VAC, 60 Hz Motor for R8800,
T1900, T1970, and T8800 Series



WG733-14DMX
208-277 VAC, 60 Hz Motor for R8800,
T1900, T1970, and T8800 Series



156T2978A
Package Accessory Trippers



WG736-14D
480 V, 60 Hz Motor for T1900, T8800,
R8800 Series