

## Mechanical Time Switch - 24-Hour Mechanical Time Switch, 480 VAC, 60Hz, DPST, Indoor/Outdoor Metal Enclosure, 1 Hour Interval

Item T1205R



### PRODUCT DESCRIPTION

The T100 Series Mechanical Time Switch has proven it can stand the test of time. These dependable time switches can handle electrical loads up to 40 A per pole and allow for up to 12 ON/OFF operations per day. A manual override switch provides added convenience.

### FEATURES

- ▶ Direct 24-hour control of most loads
- ▶ Up to 12 ON/OFF operations each day with minimum ON/OFF times of one hour
- ▶ Manual override
- ▶ One ON and one OFF tripper included
- ▶ Can be installed in most Intermatic enclosures

### APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control

### TECHNICAL DATA

#### General

Model Number	T1205R
Description	24-Hour Mechanical Time Switch, 480 VAC, 60Hz, DPST, Indoor/Outdoor Metal Enclosure, 1 Hour Interval
UPC Code	078275102255
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

#### Control Specifications

Minimum ON/OFF Times	1 hour
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
Application Compatibilities	LED; HID
On Events	12
Off Events	12
Total Events	24

#### Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R metal
Number of Trippers Included	1 ON/1 OFF

#### Dimensions

Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG

Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

#### Material Specifications

Color	Gray
-------	------

#### Load Ratings

Pilot Duty (NO) Range(s)	1000 VA, 120-277 VAC
Electronic Ballast Load Ratings NO Ranges	16 A, 277 VAC
Motor Load Ratings NO Ranges	2 HP, 24 FLA @ 120 VAC; 5 HP, 28 FLA @ 240 VAC
Tungsten Incandescent Load Ratings NO Ranges	40 A, 120-277 VAC

#### Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	480 VAC, 60 Hz
Number of Circuits	1
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Hz	60

#### Packaging

Shipping Weight (lbs)	3.503
Unit Carton Dimensions (H x W x L) in	10.06 x 4 x 6.56 in

#### Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED; Green Energy
UL File Number	UL917
California Proposition 65	Lead
RoHS Certification	N/A

---

**ACCESSORIES**



156T1978AMX  
1 Set of ON/OFF Trippers for T100,  
T7000, and WH40

156T1978A  
Extra/replacement trippers 1 ON and 2  
OFF

156T1978AD12  
12 Pack of 156T1978A Trippers for  
T100, T7000, and WH40



22T338GR  
Mounting Bracket for Intermatic  
Standardized Timer Mechanisms



156T1957A  
Skipper Screws (3 per package)



WG1576-10D  
Motor-Boxed, 480 V, 60 Hz