

Electronic Timer Control - Astronomic 7-Day/365 Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor/Outdoor Plastic Enclosure

Item ET2815CP



PRODUCT DESCRIPTION

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application. These are 7-day timers with an astronomic feature.

FEATURES

- ▶ 100-hour supercapacitor eliminates the need for batteries
- ▶ Up to 96 set points or events
- ▶ Up to 50 holiday blocks with schedule capabilities
- ▶ Automatic input voltage selection from 120 to 277 VAC, 60 Hz
- ▶ Additional mode of operation turns the ON/OFF buttons into 2-hour overrides
- ▶ Configurable outputs allow the control of various voltages and applications
- ▶ Relays incorporate zero-crossing technology to extend the life of the control
- ▶ Non-volatile EEPROM memory protects programming indefinitely
- ▶ LED compatible
- ▶ USB port makes transferring and saving of schedules easy

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

TECHNICAL DATA

| General | |
|--------------------------------|--|
| Model Number | ET2815CP |
| Description | Astronomic 7-Day/365 Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor/Outdoor Plastic Enclosure |
| UPC Code | 078275148253 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 2-Year limited |

| Control Specifications | |
|-----------------------------|---------------------|
| Minimum ON/OFF Times | 1 min |
| Maximum ON/OFF Times | Indefinite |
| Time Presets | Flexible |
| Operation Features | Astronomic; Holiday |
| Operation Mode | 7 day |
| Daylight Savings Adjustment | Automatic |
| Backup Restoration Time | 30 Minutes |
| Backup Type | Supercapacitor |
| Backup Protection Time | 100 Hour |
| Application Compatibilities | LED |
| On Events | 48 |

| | |
|--------------|-------------------|
| Off Events | 48 |
| Total Events | 96 (+ Astronomic) |

Mechanical Specifications

| | |
|----------------|--|
| Enclosure Type | Indoor/outdoor type 3R plastic with see-through door |
|----------------|--|

Dimensions

| | |
|-----------------------------------|-----------------------------|
| Product Dimensions (H x W x D) in | 10 x 6.5 x 4 in |
| Wire Size Min | #14 AWG |
| Wire Size Max | #8 AWG |
| Knockout Dimensions Bottom | (2) combination 1/2" - 3/4" |
| Knockout Dimensions Back | (1) combination 1/2" - 3/4" |

Material Specifications

| | |
|---------------|---------|
| Color | Gray |
| Body Material | Plastic |

Communication Method

| | |
|----------|----|
| Has WiFi | No |
|----------|----|

Load Ratings

| | |
|---|----------------------------------|
| Magnetic Ballast (NO) Range(s) | 20 A, 120-277 VAC |
| Magnetic Ballast (NC) Range(s) | 3 A, 120-277 VAC |
| Resistive (NO) Range(s) | 20 A, 28 VDC; 20 A, 120-240 VAC |
| Resistive (NC) Range(s) | 10 A, 28 VDC; 10 A, 120-240 VAC |
| Inductive Load Ratings NC Ranges | 10 A, 120-240 VAC |
| Inductive Load Ratings NO Ranges | 20 A, 120-240 VAC |
| Electronic Ballast Load Ratings NO Ranges | 10 A, 120/277 VAC |
| Motor Load Ratings NC Ranges | 1/4 HP, 120 VAC; 1/2 HP, 240 VAC |
| Motor Load Ratings NO Ranges | 1 HP @ 120 VAC; 2 HP @ 240 VAC |
| Electronic Ballast LED | 10 A |

Electrical Specifications

| | |
|-------------------------------|--------------------|
| Voltage Selection Type | Auto-Voltage |
| Wiring Option | Terminals |
| Input Voltage Range(s) | 120-277 VAC, 60 Hz |
| Number of Circuits | 1 |
| Switch Type | SPDT |
| Maximum Power Consumption (W) | 3 W |
| Electronic Series | ET2000 Series |
| Hz | 60 |
| Amperage | 20 A |

Packaging

| | |
|---------------------------------------|---------------------|
| Shipping Weight (lbs) | 2.25 |
| Unit Carton Dimensions (H x W x L) in | 10 x 3.937 x 6.5 in |

Environmental Specifications

Temperature (operation) -40 °F to 104 °F / (-40 °C to 40 °C)

Standards and Certifications

| | |
|--|-------------------------------|
| UL Certification | cULus |
| Other Certifications and Compatibilities | LED; Title 20; Green Energy + |
| California Proposition 65 | Lead |
| RoHS Certification | N/A |

ACCESSORIES



ET-NF
RC Snubber Noise Filter 24-277 VAC for Electronic Controls