

Electronic Timer Control - 7-Day/365-Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor/Outdoor Nema 3R Metal Enclosure

Item ET2705CR



PRODUCT DESCRIPTION

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application. These are 7-day timers.

FEATURES

- ▶ 100-hour supercapacitor eliminates the need for batteries
- ▶ Up to 96 set points or events
- ▶ Up to 50 holiday blocks with schedule capabilities
- ▶ Automatic input voltage selection from 120 to 277 VAC, 60 Hz
- ▶ Additional mode of operation turns the ON/OFF buttons into 2-hour overrides
- ▶ Configurable outputs allow the control of various voltages and applications
- ▶ Relays incorporate zero-crossing technology to extend the life of the control
- ▶ Non-volatile EEPROM memory protects programming indefinitely
- ▶ LED compatible
- ▶ USB port makes transferring and saving of schedules easy

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

TECHNICAL DATA

General	
Model Number	ET2705CR
Description	7-Day/365-Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor/Outdoor Nema 3R Metal Enclosure
UPC Code	078275148093
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited
Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Operation Features	Holiday
Operation Mode	7 day
Daylight Savings Adjustment	Automatic
Backup Restoration Time	30 Minutes
Backup Type	Supercapacitor
Backup Protection Time	100 Hour
Application Compatibilities	LED
On Events	48
Off Events	48
Total Events	96

Mechanical Specifications

Enclosure Type Indoor/outdoor type 3R metal

Dimensions

Product Dimensions (H x W x D) in 10.125 x 6.5 x 3.625 in
 Wire Size Min #14 AWG
 Wire Size Max #8 AWG
 Knockout Dimensions Bottom (2) combination 1/2" - 3/4"
 Knockout Dimensions Back (1) combination 1/2" - 3/4"

Material Specifications

Color Gray
 Body Material Type 3R Indoor/Outdoor Metal Enclosure

Communication Method

Has WiFi No

Load Ratings

Magnetic Ballast (NO) Range(s) 20 A, 120-277 VAC
 Resistive (NO) Range(s) 20 A, 28 VDC; 30 A, 120-240 VAC
 Inductive Load Ratings NO Ranges 30 A, 120-240 VAC
 Electronic Ballast Load Ratings NO Ranges 10 A, 120/277 VAC
 Motor Load Ratings NO Ranges 1 HP @ 120 VAC; 2 HP @ 240 VAC
 Tungsten Incandescent Load Ratings NO Ranges 5 A, 120-277 VAC

Electrical Specifications

Voltage Selection Type Auto-Voltage
 Wiring Option Terminals
 Input Voltage Range(s) 120-277 VAC, 60 Hz
 Number of Circuits 1
 Switch Type SPST
 Maximum Power Consumption (W) 3 W
 Electronic Series ET2000 Series
 Hz 60
 Amperage 30 A

Packaging

Shipping Weight (lbs) 3.3
 Unit Carton Dimensions (H x W x L) in 10.063 x 3.625 x 6.5 in

Environmental Specifications

Temperature (operation) -40 °F to 104 °F / (-40 °C to 40 °C)

Standards and Certifications

UL Certification cULus
 Other Certifications and Compatibilities LED; Title 20; Green Energy +

California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



ET-NF
RC Snubber Noise Filter 24-277 VAC for Electronic Controls