

## Electronic Timer Control - Astronomic 7-Day 2-Circuit Electronic Control, 120-277 VAC, 2-SPST, Indoor Metal Enclosure, Mexico Sales Only

Item ET8215CMX

**NOM**

### PRODUCT DESCRIPTION

This series offers an easy way to upgrade from a basic mechanical time switch to an electronic time switch. These timers will allow for up-to-the-minute programming, battery backup for power loss, up to 28 events total, and automatic daylight saving time corrections without the need of user interaction. These are 7-day timers with an astronomic feature.

### FEATURES

- ▶ Selector switch to determine input voltage between 120-277 VAC
- ▶ Up to 28 events total
- ▶ To-the-minute accuracy
- ▶ Temporary override or permanent manual override
- ▶ Automatic Daylight Saving Time adjustment
- ▶ Astronomic models enable dusk-to-dawn scheduling

### APPLICATIONS

- ▶ Outdoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

### TECHNICAL DATA

General	
Model Number	ET8215CMX
Description	Astronomic 7-Day 2-Circuit Electronic Control, 120-277 VAC, 2-SPST, Indoor Metal Enclosure, Mexico Sales Only
UPC Code	078275089761
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications	
Minimum ON/OFF Times	1 min
Minimum Pulse Time	3 sec
Maximum Pulse Time	3 sec
Maximum ON/OFF Times	Indefinite
Operation Features	Astronomic
Operation Mode	7 day
Daylight Savings Adjustment	Automatic
Backup Type	Battery
Battery Type	AAA
Battery Service Type	Replaceable
Chemical Composition of the Battery Cell	Alkaline
On Events	14
Off Events	14
Total Events	28 (+ Astronomic)

### Mechanical Specifications

Enclosure Type Indoor type 1 metal

#### Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG

#### Communication Method

Has WiFi	No
----------	----

#### Load Ratings

Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 30 A, 120/240 VAC
Inductive Load Ratings NO Ranges	30 A, 120/240 VAC
Motor Load Ratings NO Ranges	1 HP @ 120 VAC; 2 HP @ 240 VAC
Tungsten Incandescent Load Ratings NO Ranges	5 A, 120-240 VAC

#### Electrical Specifications

Voltage Selection Type	Selector Switch
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	2
Switch Type	2xSPST, 1xDPST or Pulse
Maximum Power Consumption (W)	6 W
Electronic Series	ET8000 Series
Hz	50/60

#### Packaging

Shipping Weight (lbs)	3.001
Unit Carton Dimensions (H x W x L) in	8.001 x 3.251 x 5.251 in

#### Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

---

## ACCESSORIES



ET-NF

RC Snubber Noise Filter 24-277 VAC for Electronic Controls