

Item Bundle - Freeze Protection 4 Breaker Base Panel with 2 Timers and Thermostat for 240V Cleaner Applications, Heater Protection, Type 3R Metal Enclosure

Item PF1222TB1



PRODUCT DESCRIPTION

Protects pool/spa equipment against freeze damage.

FEATURES

- ▶ GFCI and switch mounting capabilities
- ▶ Turns pump and heater ON when outdoor temperature drops below user-adjustable setpoint on thermostat
- ▶ Heavy-duty Type 3R metal indoor/outdoor enclosure

APPLICATIONS

- ▶ Protection
- ▶ Pump Control

TECHNICAL DATA

General

| | |
|--------------------------------|---|
| Model Number | PF1222TB1 |
| Description | Freeze Protection 4 Breaker Base Panel with 2 Timers and Thermostat for 240V Cleaner Applications, Heater Protection, Type 3R Metal Enclosure |
| UPC Code | 078275141131 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|--------------------------|-----|
| Heater Protection Switch | Yes |
|--------------------------|-----|

Mechanical Specifications

| | |
|-----------------------------|----------------|
| Number of Breaker Knockouts | 4 |
| Enclosure Type | 3R Beige metal |

Dimensions

| | |
|-----------------------------------|---------------------------|
| Product Dimensions (H x W x D) in | 16.875 x 10.875 x 4.75 in |
|-----------------------------------|---------------------------|

Material Specifications

| | |
|-------|-------|
| Color | Beige |
|-------|-------|

Load Ratings

| | |
|-------------------------|--|
| Load Center Ratings | 100 A, 120-208 VAC, 60 Hz;85 A, 120-208 VAC, 60 Hz;80 A;80 A, 208 VAC, Single Phase;60 A;60 A, 208 VAC, Single Phase;125 A;125 A, 208 VAC, Single Phase;80 A, 240 VAC, 60 Hz, Single Phase;80 A, 120-240 VAC, 50 Hz;80 A, 120 VAC, 60 Hz;60 A, 240 VAC, 60 Hz, Single Phase;60 A, 120-240 VAC, 50 Hz;60 A, 120-208 VAC, 60 Hz;125 A, 240 VAC, 60 Hz, Single Phase;125 A, 120-240 VAC, 50 Hz;125 A, 120-208 VAC, 60 Hz;100 A, 240 VAC, 60 Hz, Single Phase;85 A, 240 VAC, 60 Hz, Single Phase |
| Resistive (NO) Range(s) | 17 A, 240 VAC |

| | |
|------------------------------|--|
| Load Center Rating Display | 60 A Max, 120/240 VAC, Single Phase, 60 Hz |
| Motor Load Ratings NO Ranges | 3 HP @ 240 VAC |

Electrical Specifications

| | |
|---------------------------------------|------|
| Number of Circuits | 2 |
| Switch Type | DPST |
| Maximum Power Consumption (W) | 3 W |
| Number of Receptacle/Switch Knockouts | 2 |
| Hz | 60 |

Packaging

| | |
|---------------------------------------|-------------------------|
| Shipping Weight (lbs) | 18.712 |
| Unit Carton Dimensions (H x W x L) in | 6.25 x 12.25 x 18.25 in |

Operating Specifications

| | |
|-------------------------------|-----|
| Thermostat Range Minimum (°C) | 0.5 |
| Thermostat Range Minimum (°F) | 33 |
| Thermostat Range Maximum (°C) | 6 |
| Thermostat Range Maximum (°F) | 42 |

Standards and Certifications

| | |
|--|--------------|
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | Lead |
| RoHS Certification | N/A |

ACCESSORIES



156T1978A
Extra/replacement trippers 1 ON and 2 Spacer-Standoff, 3" long - 2 pack
OFF



21T166A



21T156A
Spacer-Standoff, 3" long - 4 pack

130LV1091
Terminal Block 2-Pole