

Surge Protection Device - Surge Protective Device, 4-Mode, 440/480 VAC 3Ph Delta, Type 1, Audible Alarm, Form C Contact, Surge Current Rating 100kA

Item L10F13N4DG2



PRODUCT DESCRIPTION

Intermatic PANELGUARD® Surge Protective Devices are designed to react quickly and eliminate surges providing optimal protection to downstream equipment. PANELGUARD Industrial/Commercial-grade series are Parallel Connected Surge Protective Devices designed to protect all types of loads fed from individual disconnects, sub-panels, distribution panels and service entrance locations.

FEATURES

- ▶ Type 1 surge protection
- ▶ Optional audible alarm and dry relay contacts
- ▶ 4 Modes of protection
- ▶ NEMA 4X enclosure for indoor or outdoor installation
- ▶ Individually integrated disconnect TPMOV surge protection technology
- ▶ Blue LED protection status indicator, and red LED service indicator
- ▶ UL Listed to ANSI/UL 1449 5th Edition

APPLICATIONS

- ▶ Distribution Panel
- ▶ Service Entrance

TECHNICAL DATA

General	
Model Number	L10F13N4DG2
Description	Surge Protective Device, 4-Mode, 440/480 VAC 3Ph Delta, Type 1, Audible Alarm, Form C Contact, Surge Current Rating 100kA
UPC Code	078275151888
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	5-Year limited
Electrical Specifications	
Modes of Protection	4
Short Circuit Current Rating	200 kA
Nominal Discharge Current	20 kA
Maximum Surge Current Rating Per Phase	100 kA
Maximum Surge Current Rating Per Mode	100 kA
Surge Protection Technology	Individually integrated thermal disconnect technology TPMOV
Maximum Continuous Operating Voltage (L-G)	552
Maximum Continuous Operating Voltage (L-L)	552
Voltage Protection Rating (L-G)	1800
Voltage Protection Rating (L-L)	4000
Voltage	440/480 VAC 3-Phase Delta
Control Specifications	
Surge Protection Type	1
Surge Protection LED Indicator	Yes

Mechanical Specifications

Enclosure Type NEMA Type 4X

Dimensions

Product Dimensions (H x W x D) in 10.59 x 5.25 x 3.29 in

Wire Lead Length (in) 18"

Wire Size Max #10 AWG

Conduit Size 3/4"

Material Specifications

Color Gray

Diagnostics Monitoring

Diagnostics Indicator Blue LED Protection Status Indicator; Red LED Service Indicator; Audible Alarm Indicator; Form C Dry Relay Contacts

Packaging

Shipping Weight (lbs) 0.6

Unit Carton Dimensions (H x W x L) in 4.375 x 6.375 x 12.625 in

Product Weight (lbs) 0.6

Product Weight (kg) 0.27

Environmental Specifications

Temperature (operation) -40 °F to 176 °F / (-40 °C to 80 °C)

Filter No Filter

Standards and Certifications

UL Certification cULus

Other Certifications and Compatibilities 2020 National Electric Code, Article 242 (previously NEC, Art. 285), 700.10 & 708.20; ANSI/IEEE C62.72-2016, ANSI/IEEE C62.41.1, C62.41.2-2002; C62.45-2002, ANSI/IEEE C62.62-2010 environments: Categories: A, B & C; Green Energy

UL Standard ANSI/UL 1449 5th Edition

California Proposition 65 Lead

RoHS Certification Y