

Plug-In Timer - 7-Day Indoor Digital Plug-In Timer

Item DT620



PRODUCT DESCRIPTION

Full feature plug-in timer provides full 7-day programming with astronomical clock and Daylight Saving Time (DST) adjustment in a convenient plug-in for quick and easy automation.

FEATURES

- ▶ 28 ON/OFF programmable events
- ▶ Full 7-day programming options, including astronomical clock, automatic DST adjustment and random mode
- ▶ Two grounded receptacles and a grounded plug
- ▶ LR44 battery backup (included)
- ▶ Plugs directly into wall outlet

APPLICATIONS

- ▶ Air Movement & Ventilation
- ▶ Indoor Lighting Control

TECHNICAL DATA

General

Model Number	DT620
Description	7-Day Indoor Digital Plug-In Timer
UPC Code	078275125322
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Minimum ON/OFF Times	1 min
Operation Features	Astronomic
Operation Mode	7 day
Backup Type	Battery
Battery Type	LR44
Battery Service Type	Replaceable
Mechanism Type	Digital/Electrical
Application Compatibilities	CFL; LED
Chemical Composition of the Battery Cell	Alkaline
On Events	28
Off Events	28
Total Events	28

Mechanical Specifications

Number of Plugs	2
Plug Configurations	5-15

Dimensions

Product Dimensions (H x W x D) in	3.2 x 3.33 x 2.25 in
-----------------------------------	----------------------

Material Specifications

Color	White
-------	-------

Load Ratings

Inductive Load Ratings NO Ranges	12 A, 120 VAC
Motor Load (NO) Range(s)	1/2 HP @ 120 VAC
Resistive Heater	15 A, 120 VAC
Tungsten Incandescent (NO) Range(s)	1000 W, 120 VAC

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
------------------------	----------------

Packaging

Shipping Weight (lbs)	0.509
Unit Carton Dimensions (H x W x L) in	3.375 x 3.375 x 3.062 in

Environmental Specifications

Usage Environments	Indoor
--------------------	--------

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	None
RoHS Certification	N/A