

## Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 208-277 V, Mexico Sales Only

Item K4223CMX



### PRODUCT DESCRIPTION

These photocontrols are provided with a swivel arm for easy and flexible installation to standard outdoor light fixtures or electrical boxes.

### FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Delay feature prevents unwanted OFF switching
- ▶ High strength, UV resistant plastic housing
- ▶ Swivel with 1/2"-14 NPSM threaded stem
- ▶ Washer gasket and locking nut included
- ▶ #18 AWG, 6" wire leads

### APPLICATIONS

- ▶ Outdoor Lighting Control

### TECHNICAL DATA

General	
Model Number	K4223CMX
Description	Stem and Swivel Mount Thermal Photocontrol, 208-277 V, Mexico Sales Only
UPC Code	078275056954
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications	
Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc
Photocontrol Type	Thermal
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Stem and Swivel Mount
Photocontrol Sensor Location	Side

Dimensions	
Product Height (in)	5
Product Height (mm)	139.7
Product Width (in)	1.563
Product Width (mm)	39.7
Product Depth (in)	1.563
Product Depth (mm)	39.7
Wire Lead Length (in)	9
Wire Lead Length (mm)	228.6
Wire Size Max	#18 AWG

**Material Specifications**

Color	Gray
Housing Material	Polycarbonate

**Load Ratings**

Magnetic Ballast (NO) Range(s)	8.3 A, 1700-2300 VA
Tungsten Incandescent (NO) Range(s)	15 A, 3100-4150 W

**Electrical Specifications**

Wiring Option	Wire leads
Input Voltage Range(s)	208-277 VAC, 50/60 Hz

**Packaging**

Shipping Weight (lbs)	0.299
Unit Carton Dimensions (H x W x D) in	4.88 x 1.75 x 3 in

**Operating Specifications**

Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650

**Environmental Specifications**

Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
Usage Environments	Outdoor

**Standards and Certifications**

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	NOM; Title 20
California Proposition 65	None
RoHS Certification	N/A

---

## ACCESSORIES



K42-SW-A  
Swivel Arm Accessory for EK4136S, K4100  
Series Stem Mount Photocontrols



22LG116  
Light Guard Accessory for K4100 Series, K4200  
Series Thermal Photocontrols



6LV1352  
Light Shield Accessory for EK4036S,  
EK4436SM, K4000 Series Button Photocontrols