

## In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 2,4,8,12 Hour, With Hold, White

Item EI230W



### PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

### FEATURES

- ▶ No programming required.
- ▶ Provides silent operation in time ranges from Two hours to 12 hours.
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation.
- ▶ Replaces single-pole switches in a variety of applications.
- ▶ Incandescent/fluorescent/CFL/LED compatible.
- ▶ For use with decorator-style wall plate (not included).
- ▶ Requires neutral connection.

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

| General                           |  |
|-----------------------------------|--|
| Model Number                      | EI230W   |
| Description                       | Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 2,4,8,12 Hour, With Hold, White |
| UPC Code                          | 078275095298   |
| Brand                             | Intermatic   |
| Country of Origin (Intermatic)    | CHINA  |
| Warranty Period                   | 1-Year limited   |
| TARIC HS Code                     | 9107.00.00   |
| Control Specifications            |  |
| Time Presets                      | 2 hrs; 4 hrs; 8 hrs; 12 hrs  |
| Operation Mode                    | Countdown  |
| Countdown Time                    | 12 hrs   |
| Hold Mode Included                | Yes  |
| Mechanism Type                    | Digital/Electrical   |
| Application Compatibilities       | Incandescent; Fluorescent; CFL; LED  |
| On Events                         | 1  |
| Total Events                      | 1  |
| Mechanical Specifications         |  |
| Wall Plate Configurations         | Single-Gang  |
| Dimensions                        |  |
| Product Dimensions (H x W x D) in | 4.125 x 1.688 x 1.438 in   |

**Material Specifications**

|                     |       |
|---------------------|-------|
| Color               | White |
| Includes Wall Plate | No    |
| Finish              | Gloss |

**Load Ratings**

|                                     |              |
|-------------------------------------|--------------|
| Resistive Heater                    | 15 A, 1800 W |
| Electronic Ballast LED              | 4 A, 500 VA  |
| Magnetic Ballast (NO) Range(s)      | 8 A, 1000 VA |
| Tungsten Incandescent (NO) Range(s) | 1000 W       |

**Electrical Specifications**

|                             |                |
|-----------------------------|----------------|
| Input Voltage Range(s)      | 120 VAC, 60 Hz |
| Wiring Configurations       | Single         |
| Neutral Connection Required | Yes            |
| Watts                       | 1800           |

**Environmental Specifications**

|                         |                         |
|-------------------------|-------------------------|
| Temperature (operation) | 32 - 104 °F / 0 - 40 °C |
|-------------------------|-------------------------|

**Packaging**

|                                       |                    |
|---------------------------------------|--------------------|
| Shipping Weight (lbs)                 | 0.349              |
| Unit Carton Dimensions (H x W x D) in | 4.88 x 3 x 2.13 in |

**Standards and Certifications**

|  |              |
|--|--------------|
| UL Certification                         | cULus        |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | DEHP         |
| RoHS Certification                       | Y            |