

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Ivory, Mexico Sales Only

Item EI210MX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required.
- ▶ Provides silent operation in time ranges from 10 minutes to 1 hour.
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation.
- ▶ Replaces single-pole switches in a variety of applications.
- ▶ Incandescent/fluorescent/CFL/LED compatible.
- ▶ For use with decorator-style wall plate (not included).
- ▶ Requires neutral connection.

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI210MX
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Ivory, Mexico Sales Only
UPC Code	078275095229
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Time Presets	10 min; 20 min; 30 min; 60 min
Operation Mode	Countdown
Countdown Time	60 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in



Material Specifications		
Color		Ivory
Load Ratings		
Resistive Heater		15 A, 1800 W
Electronic Ballast LED		500 VA
Magnetic Ballast (NO) Range(s)		8 A, 1000 VA
Tungsten Incandescent (NO) Range(s)		1000 W
Electrical Specifications		
Input Voltage Range(s)		120 VAC, 60 Hz
Wiring Configurations		Single
Neutral Connection Required		Yes
Environmental Specifications		
Temperature (operation)		32 - 104 °F / 0 - 40 °C
Packaging		
Shipping Weight (lbs)		0.35
Unit Carton Dimensions (H x W x D) in		4.88 x 3 x 2.13 in
Standards and Certifications		
UL Certification		cULus
Other Certifications and Compatibilities		NOM
California Proposition 65		None
RoHS Certification		N/A