

Electronic Timer Control - All-Purpose Photocontrol Contractor Box, 208-220 VAC 50/60 Hz; 208-240 VAC 60 Hz, DPST, Outdoor Metal Enclosure

Item PCCB32A2PLC4513MX



PRODUCT DESCRIPTION

The PCCB32A2PLC4513MX all-purpose Photocontrol Contractor box provides an easy-to-install solution for a variety of application needs. It comes with a pre-installed 3-pin photocontrol receptacle, 32 A 2-pole Contactor, 40 A 2-pole circuit breaker, and Twist Lock Photocontrol.

FEATURES

- Built-in 32 A 2-pole contactor.
- Built-in 40 A 2-pole circuit breaker for turning off the load that is being controlled.
- Built-in 3-pin photocontrol receptacle.
- Twist-lock photocontrol operated (included).

TECHNICAL DATA

General	
Model Number	PCCB32A2PLC4513MX
Description	All-Purpose Photocontrol Contractor Box, 208-220 VAC 50/60 Hz; 208-240 VAC 60 Hz, DPST, Outdoor Metal Enclosure
UPC Code	078275157736
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Operation Features	Photocontrol Operated
On Events	Photocontrol Operated
Off Events	Photocontrol Operated
Total Events	Photocontrol Operated
Mechanical Specifications	
Enclosure Type	Indoor/outdoor type 3R metal
Dimensions	
Product Height (in)	11.12
Product Height (mm)	284.48
Product Width (in)	9.6
Product Width (mm)	243.84
Product Depth (in)	4
Product Depth (mm)	101.6
Wire Size Min	Contactors #14 AWG, Circuit Breaker #14 AWG
Wire Size Max	Contactors #10 AWG, Circuit Breaker #6 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Left	(1) combination 1/2" - 3/4"



Knockout Dimensions Right

(1) combination 1/2" - 3/4"

Material Specifications	
Color	Gray
Body Material	Metal
Communication Method	
Has WiFi	No
Load Ratings	
Resistive (NO) Range(s)	32 A
General Purpose (NO) Range(s)	32 A
Electrical Specifications	
Wiring Option	Wire leads
Input Voltage Range(s)	208-220 VAC 50/60 Hz; 208-240 VAC, 60 Hz
Switch Type	DPST
Packaging	
Shipping Weight (lbs)	8.5
Unit Carton Dimensions (H x W x D) in	6.75 x 12.5 x 14.5 in
Standards and Certifications	
Other Certifications and Compatibilities	Green Energy
California Proposition 65	None
RoHS Certification	N/A