

Occupancy Sensor - Commercial Grade In-Wall PIR Occupancy/Vacancy Sensor, White, Mexico Sales Only

Item IOS-DOV-WHMX

**NOM**

PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. The sensor switch can turn a load ON and hold it as long as the sensor detects occupancy. After no motion is detected for the set time delay, the load turns OFF automatically. The sensor switch has one relay (equal to single pole switch), it also includes Ambient Light Level Sensor.

FEATURES

- ▶ Passive Infrared (PIR) sensing for presence detection.
- ▶ Coverage: 180°, 1200 ft² with non-obstructed views.
- ▶ User-selectable Vacancy or Occupancy switch mode.
- ▶ Zero-crossing technology for long life and performance.
- ▶ Adjustable ambient light sensor override.
- ▶ Incandescent/Fluorescent/CFL compatible.
- ▶ IOS-DOV models require a neutral connection.
- ▶ Fits standard decorator wall plate (included).
- ▶ Adjustable Sensitivity Settings: (30% - 100%).
- ▶ Automatic ON/OFF Control.

APPLICATIONS

- ▶ Indoor Sensing Control

TECHNICAL DATA

| General | |
|--|---|
| Model Number | IOS-DOV-WHMX |
| Description | Commercial Grade In-Wall PIR Occupancy/Vacancy Sensor, White, Mexico Sales Only |
| UPC Code | 078275125209 |
| Brand | Intermatic |
| Warranty Period | 5-Year limited |
| Country of Origin (Intermatic) | CHINA |
| Control Specifications | |
| Sensor Switch Type | Occupancy; Vacancy |
| Sensor Technology | PIR (Passive Infrared); Zero-crossing |
| PIR Coverage Area (sq ft) | 1200 |
| Application Compatibilities | Incandescent; Fluorescent; CFL |
| Adjustable Ambient Light Level Detection | 30 lux to daylight |
| Adjustable Time Delay | 15 sec to 30 min |
| Adjustable Sensitivity Settings | 30%-100% |
| Mechanical Specifications | |
| PIR Coverage Pattern (degrees) | 180 |
| Maximum Mounting Height (ft) | 4 ft |
| Mount Type | In-Wall |
| Dimensions | |
| Product Height (in) | 2.625 |

| | |
|---------------------|-------|
| Product Height (mm) | 67 |
| Product Width (in) | 1.313 |
| Product Width (mm) | 33 |
| Product Depth (in) | 1.75 |
| Product Depth (mm) | 44 |

Material Specifications

| | |
|---------------------|-------|
| Color | White |
| Includes Wall Plate | Yes |
| Finish | Gloss |

Load Ratings

| | |
|-------------------------------------|----------------|
| Magnetic Ballast (NO) Range(s) | 800 VA |
| Tungsten Incandescent (NO) Range(s) | 800 W, 120 VAC |

Electrical Specifications

| | |
|-----------------------------|--------------------|
| Input Voltage Range(s) | 120/125 VAC, 60 Hz |
| Occupancy Sensor Power Type | Line Voltage |
| Number of Circuits | 1 |
| Neutral Connection Required | Yes |
| Watts | 800 |

Packaging

| | |
|---------------------------------------|-----------------|
| Shipping Weight (lbs) | 0.4 |
| Shipping Weight (kg) | 0.181 |
| Unit Carton Dimensions (H x W x L) in | 5 x 2.25 x 3 in |

Environmental Specifications

| | |
|-------------------------|-----------------------|
| Temperature (operation) | 32 - 131°F / 0 - 55°C |
|-------------------------|-----------------------|

Standards and Certifications

| | |
|--|------|
| Other Certifications and Compatibilities | NOM |
| California Proposition 65 | None |
| RoHS Certification | N/A |