

24-Hour 208/240V Electromechanical Timer, 15 Minute Intervals, 21A, SPDT, Type 3R Outdoor Plastic Enclosure

Item GMXST-O-240



APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	GMXST-O-240
Description	24-Hour 208/240V Electromechanical Timer, 15 Minute Intervals, 21A, SPDT, Type 3R Outdoor Plastic Enclosure
UPC Code	614573013222
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
IGCC	5193
UNSPSC	39122208
Control Specifications	
Maximum Cycle Time	24 hrs
Timing Interval	15 min
Clock Drive Type	Synchronous
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Override Switch	Yes
Has Real-time Clock Face	Yes
Application Compatibilities	CFL; Fluorescent; Incandescent
Mechanical Specifications	
Mounting Options	Wall
Enclosure Type	Outdoor type 3R plastic
Has Finger-Safe Terminals	Yes
Dimensions	
Product Dimensions (H x W x D) mm	254 x 165 x 95 mm
Product Dimensions (H x W x D) in	10 x 6 1/2 x 3 3/4 in
Wire Size Max	#12 AWG
Load Ratings	

Motor Load (NO) Range(s)	1 HP @ 120 VAC; 2 HP @ 250 VAC
Tungsten Incandescent (NO) Range(s)	1350 W, 120 VAC

Electrical Specifications

Maximum Power Consumption (VA)	1
Wiring Option	Screw terminal accepts up to #12 AWG wire
Switch Type	SPDT

Display and Format

Shortest switching time	ON/OFF 15 minutes
-------------------------	-------------------

Packaging

Shipping Weight (kg)	0.706
Shipping Weight (lbs)	1.557
Unit Carton Dimensions (H x W x D) in	4.125 x 6.875 x 10.125 in
Units Per Pallet	198

Environmental Specifications

Operating Humidity	0 to 95%, Non-condensing
Temperature (operation)	-40 - 85 °C / -40 - 185 °F

Standards and Certifications

UL Certification	cULus
UL File Number	E10694
California Proposition 65	None