

24-Hour or 7-Day 24V Electronic Time Control, 16A, 20 Setpoint Programs, SPDT, Type 3R Outdoor Plastic Enclosure

Item GMXFM1D20-O-24



APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	GMXFM1D20-O-24
Description	24-Hour or 7-Day 24V Electronic Time Control, 16A, 20 Setpoint Programs, SPDT, Type 3R Outdoor Plastic Enclosure
UPC Code	078275121492
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
IGCC	5191
UNSPSC	39122208
Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	23 hours, 59 minutes
Operation Mode	24 hour; 7 day
Daylight Savings Adjustment	Manual
Backup Type	Battery
Backup Protection Time	7 Years
Battery Service Type	Non-Replaceable; Non-Rechargeable
Mechanism Type	Digital/Electrical
Has Manual Override Status Indication	Yes
On Events	10
Off Events	10
Total Events	20
Mechanical Specifications	
Enclosure Type	Outdoor type 3R plastic
Has Finger-Safe Terminals	Yes

Dimensions	
Product Dimensions (H x W x D) mm	254 x 165.1 x 25.4 mm
Product Dimensions (H x W x D) in	10 x 6.5 x 3.74 in
Wire Size Max	#10 AWG
Load Ratings	
Magnetic Ballast (NO) Range(s)	8 A, 240 VAC; 12 A, 120 VAC
Resistive (NO) Range(s)	16 A, 277 VAC
Resistive (NC) Range(s)	16 A, 277 VAC; 8 A, 24 VDC
Pilot Duty (NO) Range(s)	360 VA, 120 VAC; 720 VA, 240 VAC
Pilot Duty (NC) Range(s)	360 VA, 120 VAC
Tungsten Incandescent (NO) Range(s)	600 W, 120 VAC; 1000 W, 240 VAC
Electrical Specifications	
Maximum Power Consumption (VA)	4
Voltage Selection Type	Voltage Specific
Wiring Option	Screw box lug
Input Voltage Range(s)	24 VAC/VDC, 50/60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	1.4 W
Packaging	
Shipping Weight (kg)	0.72
Shipping Weight (lbs)	1.587
Unit Carton Dimensions (H x W x D) in	4.125 x 6.875 x 10.125 in
Units Per Pallet	108
Operating Specifications	
Expected Lifetime (Operations)	6000
Environmental Specifications	
Operating Humidity	0-95% RH, Non-condensing
Display Operating Temperature Min (°F)	-13
Display Operating Temperature Min (°C)	-25
Temperature (operation)	-25 - 55 °C / -13 - 131 °F
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	CA Title 20
UL File Number	#E10694
California Proposition 65	None
RoHS Certification	Y