

7-Day 208/240V Electromechanical Timer, 2 Hour Intervals, 21A, SPDT, Type 3R Outdoor Plastic Enclosure

Item GMXSW-O-240



APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	GMXSW-O-240
Description	7-Day 208/240V Electromechanical Timer, 2 Hour Intervals, 21A, SPDT, Type 3R Outdoor Plastic Enclosure
UPC Code	614573013628
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
IGCC	5193
UNSPSC	39122208
Control Specifications	
Maximum Cycle Time	7 days
Timing Interval	2 hrs
Clock Drive Type	Synchronous
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Override Switch	Yes
Has Real-time Clock Face	Yes
Application Compatibilities	CFL; Fluorescent; Incandescent
Mechanical Specifications	
Mounting Options	Wall
Enclosure Type	Outdoor type 3R plastic
Has Finger-Safe Terminals	Yes
Dimensions	

Product Dimensions (H x W x D) mm	254 x 165 x 95 mm
Product Dimensions (H x W x D) in	10 x 6 1/2 x 3 3/4 in
Wire Size Max	#12 AWG

Load Ratings

Motor Load (NO) Range(s)	1 HP @ 120 VAC; 2 HP @ 250 VAC
Tungsten Incandescent (NO) Range(s)	1350 W, 120 VAC

Electrical Specifications

Maximum Power Consumption (VA)	1
Wiring Option	Screw terminal accepts up to #12 AWG wire
Switch Type	SPDT

Display and Format

Shortest switching time	ON/OFF 2 hours
-------------------------	----------------

Packaging

Shipping Weight (kg)	0.715
Shipping Weight (lbs)	1.577
Unit Carton Dimensions (H x W x D) in	4.125 x 6.875 x 10.125 in
Units Per Pallet	198

Environmental Specifications

Operating Humidity	0 to 95%, Non-condensing
Temperature (operation)	-40 - 85 °C / -40 - 185 °F

Standards and Certifications

UL Certification	cULus
UL File Number	E10694
California Proposition 65	None