

Plug-In Timer - Outdoor Mechanical Plug-In Timer with Built-In Enclosure

Item P1101



PRODUCT DESCRIPTION

These plug-in timers are grounded and utilize a flip-open enclosure rated for outdoor use. These heavy-duty timers are great for providing timer function to pumps, landscaping or holiday lighting. 24-hour timers come with 2 On and 2 Off settings.

FEATURES

- ▶ 2 ON/2 OFF settings per day with removable trippers, more ON/OFF events with addition of extra trippers.
- ▶ Minimum 30-min ON/OFF time.
- ▶ Built into outdoor rated enclosure with clear or black flip cover.
- ▶ Grounded standard NEMA 5-15 plug and receptacle.
- ▶ Plugs directly into wall outlet.

APPLICATIONS

- ▶ Outdoor Lighting Control
- ▶ Landscape Water Control
- ▶ Pool Pump
- ▶ Outdoor Water Fountains

TECHNICAL DATA

| General                           |                                                          |
|-----------------------------------|----------------------------------------------------------|
| Model Number                      | P1101                                                    |
| Description                       | Outdoor Mechanical Plug-In Timer with Built-In Enclosure |
| UPC Code                          | 078275061118                                             |
| Brand                             | Intermatic                                               |
| Country of Origin (Intermatic)    | MEXICO                                                   |
| Warranty Period                   | 1-Year limited                                           |
| TARIC HS Code                     | 9107.00.00                                               |
| Control Specifications            |                                                          |
| Minimum ON/OFF Times              | 30 min                                                   |
| Operation Mode                    | 24 hour                                                  |
| Mechanism Type                    | Analog/Mechanical                                        |
| Application Compatibilities       | Incandescent; Tungsten                                   |
| On Events                         | 24                                                       |
| Off Events                        | 24                                                       |
| Total Events                      | 48                                                       |
| Mechanical Specifications         |                                                          |
| Plug Configurations               | 5-15                                                     |
| Mount Type                        | Plug-In                                                  |
| Dimensions                        |                                                          |
| Product Dimensions (H x W x D) in | 5.375 x 5.125 x 2.5 in                                   |
| Cord Size                         | 22"                                                      |
| Material Specifications           |                                                          |



ColorBlack and Clear

| Load Ratings                        |                                |
|-------------------------------------|--------------------------------|
| Resistive Heater                    | 15 A, 120 VAC                  |
| Resistive (NO) Range(s)             | 15 A, 120 VAC                  |
| Motor Load (NO) Range(s)            | 1 HP, 15 FLA, 90 LRA @ 120 VAC |
| Tungsten Incandescent (NO) Range(s) | 1800 W, 120 VAC                |

| Electrical Specifications |                |
|---------------------------|----------------|
| Input Voltage Range(s)    | 120 VAC, 60 Hz |

| Packaging                             |                       |
|---------------------------------------|-----------------------|
| Shipping Weight (lbs)                 | 1.297                 |
| Unit Carton Dimensions (H x W x L) in | 7.75 x 3.81 x 5.75 in |

| Environmental Specifications |         |
|------------------------------|---------|
| Usage Environments           | Outdoor |

| Standards and Certifications             |              |
|------------------------------------------|--------------|
| CSA Certification                        | cCSAus       |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | DEHP         |
| RoHS Certification                       | N/A          |

ACCESSORIES



107TN221  
Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222  
Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS