Weather Proof Cover - Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.75" Orange

Item WP5100OR



FEATURES

- Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- CEC Article 26-702 Compliant
- UL Certified for Type 3R outdoor enclosures
- Meets requirements for cold impact testing: -60° F (-51° C)
- Heavy-duty UV stabilized polycarbonate cover, mounting base, and inserts
- 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws
- Lockable hasp: All models accept up to 1/4" (6 mm) dia shank
- Impact rated: 12 lbf. impact test to ensure cover remains intact
- Reinforced hinge pin designed to exceed 40 lbf. hinge hang/stress test
- Warranty: 1-year limited

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP5100OR
Description	Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.75" Orange
UPC Code	078275145658
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	Yes

Dimensions	
Product Dimensions (H x W x D) in	6 1/3 x 4 2/3 x 2 3/4 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single


Material Specifications	
Color	Orange
Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.5
Unit Carton Dimensions (H x W x L) in	6.5 x 2.75 x 4.75 in

Standards and Certifications	
UL Certification	cULus

CSA Certification	cCSAus
California Proposition 65	None

DRAWINGS AND DIAGRAMS



MOUNTING SCREW HOLE LOCATIONS

KEY HOLE, CENTER HOLE AND ROUND KNOCK OUT

NOTES:
1. KNOCK OUT SPACING AND DIMENSIONS SAME FOR ALL VERSIONS OF SINGLE GANG EXTRA DUTY PLASTIC.
2. BASIC DIMENSIONS ARE THE SAME FOR ALL VERSIONS.
3. DIMENSIONS ARE APPROXIMATE AND ROUNDED TO NEAREST 1/16TH".
4. SCALE 1:2.

ACCESSORIES



WP17
Single-Gang Inserts (3)