

Weatherproof Cover - Plastic In-Use Weatherproof Cover, Vertical Mount, Double-Gang, GFCI & Duplex Single-Gang Horizontal or Vertical applications, 3.125" Clear

Item WP1030C



PRODUCT DESCRIPTION

The WP1030C In-Use Weatherproof Cover provides dependable protection for electrical receptacles in outdoor, damp, and wet-location applications. Constructed from heavy-duty, UV-stabilized polycarbonate, this clear cover features a 3 mm neoprene gasket and is tested for cold impact down to -60°F (-51°C) for reliable performance in demanding environments. Included duplex and GFCI inserts can be rotated to accommodate vertical or horizontal single-device configurations on standard 4-inch square boxes, providing added installation flexibility. UL Certified for Type 3R outdoor enclosures and featuring a 3.125-inch depth, the WP1030C delivers durable, versatile protection for outdoor electrical connections.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick neoprene gasket with slits for mounting screws.
- WP101 Duplex & WP102 GFCI single-gang application inserts included.
- Inserts can be rotated to fit vertical or horizontal applications.
- Fits standard square 4" wall boxes with single-gang applications.
- Max cord size: (2) #14 AWG or (1) #12 AWG, WP1050 (2) #14 AWG or (1) #10 AWG.
- Warranty: 1-year limited.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP1030C
Description	Plastic In-Use Weatherproof Cover, Vertical Mount, Double-Gang, GFCI & Duplex Single-Gang Horizontal or Vertical applications, 3.125" Clear
UPC Code	078275003231
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Included Inserts	2
Insert Types Included	WP101; WP102
Hinge Direction	Vertical
Is Extra-Duty Rated	No
Number of Gangs	Double
Electrical Box Shape	Square
Dimensions	
Product Dimensions (H x W x D) in	5.5 x 5 x 3.125 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Double
Material Specifications	



Color	Clear
Weatherproof Cover Material	UV Stabilized Plastic

Packaging

Shipping Weight (lbs)	0.899
Unit Carton Dimensions (H x W x L) in	4.25 x 6.88 x 8.88 in


Standards and Certifications

UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



WP101
Double-Gang Duplex Insert



WP102
Double-Gang GFCI Insert