In-Wall Timer - Electronic Countdown Timer, 125 VAC, 60 Hz, Preset Times 10/20/30/60/120, White, plus optional Light Almond Cover

Item EI-210-WLA

PRODUCT DESCRIPTION

5-button timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- No programming required.
- Provides silent operation in time ranges from ten minutes to two hours.
- Five-button time selection, with all models having an ON/OFF mode with Auto-OFF after 24 hours of operation.
- Replaces single-pole switches in a variety of applications.
- Interchangeable line/load leads, to simplify installations.
- "DoubleTime" dual-program mode adds versatility to top button.
- Includes a light almond faceplate for quick color change.
- Requires neutral connection.
- For use with decorator-style wall plate (not included).
- Stylish blue LED indicators count down from top to bottom as the program time elapses.

APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI-210-WLA
Description	Electronic Countdown Timer, 125 VAC, 60 Hz, Preset Times 10/20/30/60/120, White, plus optional Light Almond Cover
UPC Code	078275161566
Brand	Intermatic
Country of Origin (Intermatic)	VIETNAM
Warranty Period	2-Year limited

Control Specifications	
Time Presets	10 min; 20 min; 30 min; 1 hr; 2 hrs
Operation Mode	Countdown
Countdown Time	2 hrs
Hold Mode Included	Yes
Mechanism Type	Digital/Electronic
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1

Mechanical Specifications	
Wall Plate Configurations	Single-Gang

© 10/13/2026

Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.5 in

Material Specifications	
Color	White
Includes Wall Plate	No
Finish	Gloss

Load Ratings	
Resistive Heater	15 A, 1875 W
Electronic Ballast LED	10 A
General Purpose (NO) Range(s)	15 A, 125 VAC
Tungsten Incandescent (NO) Range(s)	10 A, 1250 W

Electrical Specifications	
Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST-NO
Neutral Connection Required	Yes
Watts	1875

Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C

Packaging	
Shipping Weight (lbs)	0.47
Unit Carton Dimensions (H x W x D) in	5.11 x 2.97 x 2.56 in

Standards and Certifications	
Other Certifications and Compatibilities	Green Energy; cETLus
California Proposition 65	Bisphenol A (BPA)
RoHS Certification	N

© 10/13/2026

ACCESSORIES

EI-210COV-LA
EI-210 Light Almond Cover

EI-210COV-WH
EI-210 White Cover