Cycle Timer - Percentage Cycle Time Switch

Item CT2000



PRODUCT DESCRIPTION

The CT2000 Percentage Cycle Time Switch is a field adjustable timer, offering true flexibility for repetitive cycle times via an upfront control button. The timer provides repetitive cycling for short-cycle applications. The timer enclosure includes two slotted mounting holes on 5" centers and a ½" knockout for conduit connection.

FEATURES

- Provides 8 field-selectable cycle durations of 30 seconds, 1, 3, 5, 10, 30 minutes and 1 or 4 hours.
- Front cover button enables true flexibility for repetitive cycle times.
- Temporary and permanent manual overrides.
- 30 separate positions enable precise percentage ON time selection.
- User settings stored in non-volatile memory.
- No DIP switches to program cycle time.
- Type 3R indoor/outdoor aluminum enclosure.

APPLICATIONS

- Agriculture Feeders
- Greenhouse Misting Control

TECHNICAL DATA

General	
Model Number	CT2000
Description	Percentage Cycle Time Switch
UPC Code	078275124363
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Cycle Duration	30 sec; 1 min; 3 min; 5 min; 10 min: 30 min; 1-Hour; 4 hours
Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal
Dimensions	
Product Dimensions (H x W x D) in	6.625 x 3.5 x 3.313 in
Material Specifications	
Color	Gray
Load Ratings	
Pilot Duty (NO) Range(s)	470 VA, 240 VAC
General Purpose (NO) Range(s)	20 A, 240 VAC
Motor Load (NO) Range(s)	1 HP @ 120 VAC; 2 HP @ 240 VAC
Electrical Specifications	

Technical specifications and other information are subject to change without notice. Images can vary from original.

Wiring Option	Wire leads
Switch Type	SPST

Packaging	
Shipping Weight (lbs)	1.397
Unit Carton Dimensions (H x W x L) in	4.06 x 4 x 7.38 in

Environmental Specifications	
Temperature (operation)	-14 °F to 140 °F / (-10 °C to 60 °C)

Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.