In-Wall Timer - Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, Ivory, Mexico Sales Only

Item EI400CMX



PRODUCT DESCRIPTION

Offering a programmable countdown time between one second and 24 hours, this versatile timer can handle any application, regardless of load type. No neutral connection is required. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- Programmable countdown time interval from one second to 24 hours.
- Settings stored in non-volatile memory.
- Optional audible and/or visual warning of impending load switch OFF.
- Lockable settings help avoid unintended changes.
- Single-pole or 3-way switch compatible installation.
- Incandescent/fluorescent/CFL/LED compatible.
- Isolated switch allows timer to be used with any load type including AC and DC loads.
- Replaceable CR2 lithium battery provides up to three years of operation.
- No neutral wire connection enables easy retrofitting and quicker installation.
- 24-hour programming allows for continuous operation.

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI400CMX
Description	Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, Ivory, Mexico Sales Only
UPC Code	078275101371
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	5-Year limited
TARIC HS Code	9107.00.00

Control Specifications	
Operation Mode	Countdown
Countdown Time	1 sec; 24 hrs
Mechanism Type	Digital/Electronic
Backup Type	Battery
Backup Protection Time	3 Years
Battery Type	CR2 Lithium
Battery Service Type	Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications	
Wall Plate Configurations	Single-Gang

Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.188 in

Material Specifications	
Color	Ivory

Load Ratings	
Resistive Heater	20 A, 2400-5540 W, 120-277 VAC
DC Loads	4 A, 12 VDC; 2 A, 28 VDC
Inductive Load Ratings NO Ranges	16 A, 120-277 VAC
Tungsten Incandescent (NO) Range(s)	1800 W, 120 VAC; 1248-1662 W, 208-277 VAC

Electrical Specifications	
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Wiring Configurations	Single; 3-Way

Environmental Specifications	
Temperature (operation)	32 - 122 °F / 0 - 50 °C

Packaging	
Shipping Weight (lbs)	0.399
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.