In-Wall Timer - Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, White

Item EI400WC



PRODUCT DESCRIPTION

Offering a programmable countdown time between one second and 24 hours, this versatile timer can handle any application, regardless of load type. No neutral connection is required. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- Programmable countdown time interval from one second to 24 hours.
- Settings stored in non-volatile memory.
- Optional audible and/or visual warning of impending load switch OFF.
- Lockable settings help avoid unintended changes.
- Single-pole or 3-way switch compatible installation.
- Incandescent/fluorescent/CFL/LED compatible.
- Isolated switch allows timer to be used with any load type including AC and DC loads.
- Replaceable CR2 lithium battery provides up to three years of operation.
- No neutral wire connection enables easy retrofitting and quicker installation.
- 24-hour programming allows for continuous operation.

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI400WC
Description	Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, White
UPC Code	078275101388
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	5-Year limited
TARIC HS Code	9107.00.00

Control Specifications	
Time Presets	Programmable
Operation Mode	Countdown
Countdown Time	1 sec; 24 hrs
Mechanism Type	Digital/Electronic
Backup Type	Battery
Battery Type	CR2
Battery Service Type	Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Lithium Manganese Dioxide (LiMnO2)
Number of Batteries Included	1
Battery Weight (grams)	11
Number of Lithium-ion Cells in Battery	N/A
Number of Lithium Metal Cells in Battery	1
Watt Hours Per Battery	3.0

Technical specifications and other information are subject to change without notice. Images can vary from original.

Lithium Content (grams) in Battery	0.5
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.188 in
Material Specifications	
Color	White
Load Ratings	
Resistive Heater	20 A, 2400-5540 W, 120-277 VAC
DC Loads	4 A, 12 VDC; 2 A, 28 VDC
Inductive Load Ratings NO Ranges	16 A, 120-277 VAC
Tungsten Incandescent (NO) Range(s)	1800 W, 120 VAC; 1248-1662 W, 208-277 VAC
Electrical Specifications	
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Wiring Configurations	Single; 3-Way
Switch Type	SPST
Environmental Specifications	
Temperature (operation)	32 - 122 °F / 0 - 50 °C
Packaging	
Shipping Weight (lbs)	0.399
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in
Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.