In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 2,4,8,12 Hour, With Hold, Ivory, Mexico Sales Only

Item EI230MX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- No programming required.
- Provides silent operation in time ranges from Two hours to 12 hours.
- Single-button time selection, with some models having a HOLD mode, for continuous ON operation.
- Replaces single-pole switches in a variety of applications.
- Incandescent/fluorescent/CFL/LED compatible.
- For use with decorator-style wall plate (not included).
- Requires neutral connection.

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI230MX
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 2,4,8,12 Hour, With Hold, Ivory, Mexico Sales Only
UPC Code	078275095281
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications	
Time Presets	2 hrs; 4 hrs; 8 hrs; 12 hrs
Operation Mode	Countdown
Countdown Time	12 hrs
Hold Mode Included	Yes
Mechanism Type	Digital/Electronic
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1

Mechanical Specifications	
Wall Plate Configurations	Single-Gang

Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in

Technical specifications and other information are subject to change without notice. Images can vary from original.

Material Specifications	
Color	Ivory

Load Ratings	
Resistive Heater	15 A, 1800 W
Electronic Ballast LED	4 A, 500 VA
Magnetic Ballast (NO) Range(s)	8 A, 1000 VA
Tungsten Incandescent (NO) Range(s)	1000 W

Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C

Packaging	
Shipping Weight (lbs)	0.351
Unit Carton Dimensions (H x W x D) in	6.131 x 2.131 x 3.001 in

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.