# In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 30 Minute Max, With Hold, Ivory

Item FD30MH

## PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

## FEATURES

- 30-Minute timer with hold.
- SPST (Single-Pole Single-Throw).
- No electricity required to operate.
- Replaces any standard or decorator single- or multi-gang wall switch.
- Automatically limits ON time for energy consuming loads.
- Quick and easy installation.
- Time-saving up front terminal connection with teeter-type terminals.
- Breaks circuit at end of timing cycle.
- Incandescent/fluorescent/CFL/LED compatible.
- No neutral connection is required.

## APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Motor Control
- Air Movement & Ventilation

## TECHNICAL DATA

| General | |
|---|---|
| Model Number | FD30MH |
| Description | Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 30 Minute Max, With Hold, Ivory |
| UPC Code | 078275185586 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | TUNISIA |
| Warranty Period | 1-Year limited |
| TARIC HS Code | 9107.00.00 |

| Control Specifications | |
|---|---|
| Operation Mode | Countdown |
| Countdown Time | 30 min |
| Hold Mode Included | Yes |
| Mechanism Type | Analog/Mechanical |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |

| Mechanical Specifications | |
|---|---|
| Wall Plate Configurations | Single-Gang; Multi-Gang |

| Dimensions | |
|---|---|
| Product Dimensions (H x W x D) in | 4.125 x 1.75 x 1.25 in |

| Material Specifications | |
|---|---|
| Color | Ivory |
| Includes Wall Plate | No |

| Load Ratings | |
|---|---|
| Resistive Heater | 20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC |
| Tungsten Incandescent (NO) Range(s) | 7 A, 125 VAC, 875 W |

| Electrical Specifications | |
|---|---|
| Input Voltage Range(s) | 125-277 VAC, 50/60 Hz |
| Wiring Configurations | Single |
| Switch Type | SPST |
| Neutral Connection Required | No |

| Environmental Specifications | |
|---|---|
| Temperature (operation) | 40 - 120 °F / 4 - 49 °C |

| Packaging | |
|---|---|
| Shipping Weight (lbs) | 0.299 |
| Unit Carton Dimensions (H x W x D) in | 4.63 x 2.13 x 2.88 in |

| Standards and Certifications | |
|---|---|
| UL Certification | RU |
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | DEHP |
| RoHS Certification | N/A |

Technical specifications and other information are subject to change without notice. Images can vary from original.

## ACCESSORIES

148FD5068
Plate for 30-Min with HOLD, Ivory (FD30MH)

146--00045
Knob-Wall Switch FD Series - Ivory

146--00046
Knob-Wall Switch FD Series - White

146--00047
Knob-Wall Switch FD Series - Almond

146MT416A
Knob-Wall Switch FD Series - Black