Electronic Timer Control - Astronomic 7-Day/365-Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor/Outdoor NEMA 3R Metal Enclosure

Item ET2815CR



PRODUCT DESCRIPTION

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application. These are 7-day timers with an astronomic feature.

FEATURES

- 100-hour supercapacitor eliminates the need for batteries.
- Up to 96 set points or events.
- Up to 50 holiday blocks with schedule capabilities.
- Automatic input voltage selection from 120 to 277 VAC, 60 Hz.
- Additional mode of operation turns the ON/OFF buttons into 2-hour overrides.
- Configurable outputs allow the control of various voltages and applications.
- Relays incorporate zero-crossing technology to extend the life of the control.
- Non-volatile EEPROM memory protects programming indefinitely.
- LED compatible.
- USB port makes transferring and saving of schedules easy.

APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Timing/Scheduling ON/OFF
- Machinery & Pump Controls

TECHNICAL DATA

General	
Model Number	ET2815CR
Description	Astronomic 7-Day/365-Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor/Outdoor NEMA 3R Metal Enclosure
UPC Code	078275148246
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Time Presets	Flexible
Operation Features	Astronomic; Holiday
Operation Mode	7 day
Daylight Savings Adjustment	Automatic
Backup Restoration Time	30 Minutes
Backup Type	Supercapacitor
Backup Protection Time	100 Hour
Application Compatibilities	LED
On Events	48

Off Events	48
Total Events	96 (+ Astronomic)

Mechanical Specifications	
Enclosure Type	Indoor/outdoor type 3R metal

Dimensions	
Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

Material Specifications	
Color	Gray
Body Material	Type 3R Indoor/Outdoor Metal Enclosure

Communication Method	
Has WiFi	No

Load Ratings	
Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Magnetic Ballast (NC) Range(s)	3 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 20 A, 120-240 VAC
Resistive (NC) Range(s)	10 A, 28 VDC; 10 A, 120-240 VAC
Inductive Load Ratings NC Ranges	10 A, 120-240 VAC
Inductive Load Ratings NO Ranges	20 A, 120-240 VAC
Electronic Ballast (NO) Range(s)	10 A, 120/277 VAC
Motor Load (NC) Range(s)	1/4 HP, 120 VAC; 1/2 HP, 240 VAC
Motor Load (NO) Range(s)	1 HP @ 120 VAC; 2 HP @ 240 VAC

Electrical Specifications	
Voltage Selection Type	Auto-Voltage
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	3 W
Electronic Series	ET2000 Series

Packaging	
Shipping Weight (lbs)	3.3
Unit Carton Dimensions (H x W x L) in	10.063 x 3.625 x 6.5 in

Environmental Specifications	
Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	LED; Title 20; Green Energy +
California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



ET-NF
RC Snubber Noise Filter 24-277 VAC for Electronic Controls