Electronic Timer Control - 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor Metal Enclosure, Mexico Sales Only

Item ET1705CMX



NOM

PRODUCT DESCRIPTION

This series offers an easy way to upgrade from a basic mechanical time switch to an electronic time switch. These timers will allow for up-to-the-minute programming, battery backup for power loss, up to 28 events total, and automatic daylight saving time corrections without the need of user interaction. These are 7-day timers.

FEATURES

- Selector switch to determine input voltage between 120-277 VAC.
- Up to 28 events total.
- To-the-minute accuracy.
- Temporary override or permanent manual override.
- Automatic Daylight Saving Time adjustment.

APPLICATIONS

- Indoor Lighting Control
- Timing/Scheduling ON/OFF
- Machinery & Pump Controls

TECHNICAL DATA

General	
Model Number	ET1705CMX
Description	7-Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor Metal Enclosure, Mexico Sales Only
UPC Code	078275109841
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Operation Mode	7 day
Daylight Savings Adjustment	Automatic
Backup Type	Battery
Battery Type	AAA
Battery Service Type	Replaceable
Chemical Composition of the Battery Cell	Alkaline
On Events	14
Off Events	14
Total Events	28

Mechanical Specifications	
Enclosure Type	Indoor type 1 metal

Dimensions	
Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in

© 10/21/2026

Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

Communication Method	
Has WiFi	No

Load Ratings	
Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 30 A, 120/240 VAC
Inductive Load Ratings NO Ranges	30 A, 120/240 VAC
Motor Load (NO) Range(s)	1 HP @ 120 VAC; 2 HP @ 240 VAC
Tungsten Incandescent (NO) Range(s)	5 A, 120/240 VAC

Electrical Specifications	
Voltage Selection Type	Selector Switch
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	1
Switch Type	SPST
Maximum Power Consumption (W)	6 W
Electronic Series	ET1700 Series

Packaging	
Shipping Weight (lbs)	2.845
Unit Carton Dimensions (H x W x L) in	3.131 x 5.251 x 8.001 in

Environmental Specifications	
Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)

Standards and Certifications	
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



ETBATT-1
Battery Tray Door, ET Series



ET-NF
RC Snubber Noise Filter 24-277 VAC for Electronic Controls

124--00100
(SPST) Insulator for ET Series controls (ET1105C, ET1105CR, ET1705C, ET1705CR, ET8015C and ET8015CR)