Occupancy Sensor - Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only

Item IOS-CMP-ULCMX



NOM

PRODUCT DESCRIPTION

Este sensor de infrarrojo pasivo (PIR) detecta la diferencia del calor emitido por un cuerpo humano en movimiento y el espacio de fondo. El sensor enciende la luz controlada y la luz se mantiene encendida siempre que el sensor detecte alguna presencia. El sensor apaga la luz controlada cuando no detecta movimiento después de un tiempo de retardo ajustable.

FEATURES

- PIR technology sensing for presence detection.
- Coverage: 1200 ft2 when mounted on 8 to 11 ft ceiling.
- Zero-crossing technology for long life and performance.
- Adjustable ambient light sensor override.
- Requires neutral connection.
- Incandescent/Fluorescent/CFL/LED compatible.

APPLICATIONS

- Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-CMP-ULCMX
Description	Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only
UPC Code	078275149274
Brand	Intermatic
Warranty Period	1-Year limited
Country of Origin (Intermatic)	CHINA

Control Specifications	
Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications	
PIR Coverage Pattern (degrees)	360
Maximum Mounting Height (ft)	8-11 ft
Mount Type	Ceiling

Material Specifications	
Color	White
Includes Wall Plate	Yes
Finish	Gloss

Load Ratings	
Electronic Ballast LED	100-200 W

Technical specifications and other information are subject to change without notice. Images can vary from original.

Electrical Specifications	
Input Voltage Range(s)	120/277 VAC, 50/60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Watts	200

Packaging	
Shipping Weight (lbs)	0.72
Shipping Weight (kg)	0.327
Unit Carton Dimensions (H x W x L) in	2.25 x 5.82 x 5.82 in

Standards and Certifications	
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.