In-Wall Timer - Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, Without Hold, Silver, Mexico Sales Only

Item FF12HCMX



NOM

PRODUCT DESCRIPTION

The FF Series Commercial Countdown Timers are designed to replace any standard wall switch and do not require electricity to operate. These energy-efficient switches automatically limit the ON times for fans, lighting, motors, heaters, and other energy consuming loads. A commercial "brushed metal" look plate (plastic construction) meets NEC requirements. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- 12-Hour timer.
- SPST (Single-Pole Single-Throw).
- Breaks circuit at end of timing cycle.
- No electricity required to operate.
- Replaces any standard or decorator single-gang wall switch.
- Automatically limits ON time for energy consuming loads.
- Quick and easy installation.
- Time-saving up front terminal connection with teeter-type terminals.
- Brushed metal look switch plate meets NEC requirements (plate is included).
- Incandescent/fluorescent/CFL/LED compatible.

APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Motor Control
- Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	FF12HCMX
Description	Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, Without Hold, Silver, Mexico Sales Only
UPC Code	078275005259
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications	
Time Presets	12 hrs
Operation Mode	Countdown
Countdown Time	12 hrs
Hold Mode Included	No
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications	
Wall Plate Configurations	Single-Gang; Multi-Gang

Dimensions

Product Dimensions (H x W x D) in	4.5625 x 2.75 x 2.25 in

Material Specifications	
Color	Silver
Includes Wall Plate	Yes
Finish	Brushed Metal

Load Ratings	
Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten Incandescent (NO) Range(s)	7 A, 125 VAC, 875 W

Electrical Specifications	
Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	No

Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C

Packaging	
Shipping Weight (lbs)	0.301
Unit Carton Dimensions (H x W x D) in	7 x 4 x 2.5 in
Product Weight (lbs)	0.29
Product Weight (kg)	0.132

Standards and Certifications	
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.