Occupancy Sensor - Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only

Item IOS-CMP-UMX



NOM

PRODUCT DESCRIPTION

The IOS-CMP-U 360° Passive Infrared (PIR) Line Voltage Occupancy Sensors control lighting systems based on occupancy and ambient light levels. When movement is detected, the sensor turns the lights ON. If no movement is detected for a user-specified time, the lights are turned OFF. The occupancy sensor provides a 360° coverage pattern, up to 1200 square feet.

FEATURES

- PIR technology sensing for presence detection.
- Coverage: 1200 ft2 when mounted on 8 to 11 ft ceiling.
- Zero-crossing technology for long life and performance.
- Adjustable ambient light sensor override.
- Requires neutral connection.
- Incandescent/Fluorescent/CFL/LED compatible.

APPLICATIONS

- Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-CMP-UMX
Description	Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only
UPC Code	078275139916
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA

Control Specifications	
Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Adjustable Ambient Light Level Detection	10 fc to 150 fc
Adjustable Time Delay	15 sec to 30 min

Mechanical Specifications	
PIR Coverage Pattern (degrees)	360
Maximum Mounting Height (ft)	8-11 ft
Mount Type	Ceiling

Dimensions	
Product Height (in)	1.375
Product Height (mm)	35
Product Diameter (in)	4.563
Product Diameter (mm)	116

Technical specifications and other information are subject to change without notice. Images can vary from original.

Material Specifications	
Color	White
Includes Wall Plate	Yes
Finish	Gloss

Load Ratings	
Electronic Ballast LED	800 VA, 120/125 VAC; 1600 VA, 277 VAC
Tungsten Incandescent (NO) Range(s)	800 W, 120/125 VAC

Electrical Specifications	
Input Voltage Range(s)	120/277 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Watts	800

Packaging	
Shipping Weight (lbs)	0.4
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	2 x 5 x 5 in

Environmental Specifications	
Temperature (operation)	32 - 131°F / 0 - 55°C

Standards and Certifications	
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.